QUICK REFERENCE GUIDE > CPV3-488-N

48" Series 9 8 Burner Gas Rangetop, Natural Gas

Series 9 | Professional

Stainless Steel | Natural Gas



Eight burners for when you need maximum performance and cooktop space - great for those who love to cook for a crowd.

- Your burners can deliver anything from very high 23,500 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- · Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16 "
Width	47 7/8 "
Depth	28 "

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design Quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

SPECIFICATIONS

Burner ratings		
Maximum burner	power	Yes
Power back centr	e	18,500 BTU
Power back centr	e (2)	18,500 BTU
Power back left		18,500 BTU
Power back right		18,500 BTU
Power front centr	e	18,500 BTU
Power front centr	e (2)	18,500 BTU
Power front left		23,500 BTU
Power front right		23,500 BTU
Total cooktop pov	ver	158,000 BTU

Cleaning

Easy clean porcelain base	oan
---------------------------	-----

Controls

Metal Illuminated dials	•
Star K Certification	•

Titanium coated	d, illumina	ted metal	l dials	
-----------------	-------------	-----------	---------	--

Gas Requirements

Fitting and pipe	½ NPT, min. %″ ⊠ flex line
Supply Pressure (natural gas)	6" to 9" W.C

FISHER & PAYKEL

QUICK REFERENCE GUIDE > CPV3-488-N

Р	е	rf	0	r	m	ıa	n	С	е

Sealed cooking surface

Sealed Dual Flow Burners™

8

Simmer on all burners

140 °F

Power Requirements

Amperage 15 A
Supply frequency 60 Hz
Supply voltage 120 V

Product Dimensions

 Depth
 28 "

 Height
 8 5/16 "

 Width
 47 7/8 "

Recommended Back Guards Ventilation

Combustible situation BGCV2-3048H

Non combustible situation BGCV2-3048 / BGCV2-1248

Pro hood HCB48-12_N

Safety

ADA compliant

SKU 82981

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

Data Sheet Gas Rangetop and Low Shelf High Backguard

Data Sheet Gas Rangetop and High Shelf High Backguard

Installation Guide EN

Guide d'installation FR

Planning Guide Professional Style Dial/Handle Accessories

, Revit Gas Rangetop

Rhino Gas Rangetop

SketchUp Gas Rangetop

User Guide EN

User Guide FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com