QUICK REFERENCE GUIDE > CPV3-486GD-L

Date: 02.05.2025 > 1

48" Series 9 6 Burner with Griddle Gas Rangetop, LPG

Series 9 | Professional

Stainless Steel | LPG



A powerful six burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Griddle with burners that deliver up to 19,000 BTU heat per burner, for seriously fast boiling
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from grilled cheese to quesadillas

Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16 "
Width	47 7/8 "
Depth	28 "

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design Quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron trivets, and titanium coated dials.

SPECIFICATIONS

Burner ratings	
Maximum burner power	Yes
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	19000BTU
Power front right	15000BTU
Power griddle	15000BTU
Total cooktop power	103000BTU
Burners	
Number of burners	6
Cleaning	
Easy clean porcelain basepan	•
Controls	

Gas Requirements

Metal illuminated dials

Star K Certification

QUICK REFERENCE GUIDE > CPV3-486GD-L Date: 02.05.2025 > 2

Performance Auto re-ignition system Sealed Dual Flow Burners™ Sealed range top Simmer on all burners Power Requirements Supply frequency Supply voltage Product Dimensions Depth 48 5/16 Width Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048 BGCV2-1246 Pro hood HCB48-12_N	Fitting and pipe	½ NPT, min. 5%″ ∑ flex line
Auto re-ignition system Sealed Dual Flow Burners™ Sealed range top Simmer on all burners Power Requirements Supply frequency Supply voltage Product Dimensions Depth As 5/16 Width Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-30486 BGCV2-1246 Pro hood HCB48-12_N	Supply Pressure (LPG)	11" to 14" W.C
Sealed Dual Flow Burners™ Sealed range top Simmer on all burners Power Requirements Supply frequency Supply voltage Product Dimensions Depth Height Width Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048 BGCV2-1246 Pro hood HCB48-12_N	Performance	
Sealed range top Simmer on all burners Power Requirements Supply frequency Supply voltage Product Dimensions Depth Height Width Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048 BGCV2-1248 Pro hood HCB48-12_N	Auto re-ignition system	•
Power Requirements Supply frequency Supply voltage Product Dimensions Depth Height Width Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048H BGCV2-1244 Pro hood HCB48-12_N	Sealed Dual Flow Burners™	6
Power Requirements Supply frequency 60 H: Supply voltage 120 V Product Dimensions Depth 28 Height 8 5/16 Width 47 7/8 Recommended Back Guards Ventilation Combustible situation BGCV2-3048H Non combustible situation BGCV2-1244 Pro hood HCB48-12_N	Sealed range top	•
Supply frequency Supply voltage Product Dimensions Depth	Simmer on all burners	140 °F
Product Dimensions Depth 28 Height 8 5/16 Width 47 7/8 Recommended Back Guards Ventilation Combustible situation BGCV2-3048 Non combustible situation BGCV2-1246 Pro hood HCB48-12_N	Power Requirements	
Product Dimensions Depth 28 Height 8 5/16 Width 47 7/8 Recommended Back Guards Ventilation Combustible situation BGCV2-3048 Non combustible situation BGCV2-1246 Pro hood HCB48-12_N	Supply frequency	60 Hz
Depth 28 Height 8 5/16 Width 47 7/8 Recommended Back Guards Ventilation Combustible situation BGCV2-3048 Non combustible situation BGCV2-1246 Pro hood HCB48-12_N	Supply voltage	120 V
Height 8 5/16 Width 47 7/8 Recommended Back Guards Ventilation Combustible situation BGCV2-3048 Non combustible situation BGCV2-1246 Pro hood HCB48-12_N	Product Dimensions	
Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048 BGCV2-3048 BGCV2-1248 Pro hood HCB48-12_N	Depth	28 "
Recommended Back Guards Ventilation Combustible situation Non combustible situation BGCV2-3048H BGCV2-3048 BGCV2-1248 Pro hood HCB48-12_N	Height	8 5/16 "
Combustible situation Non combustible situation BGCV2-3048H BGCV2-3048 BGCV2-3048 BGCV2-1246 Pro hood HCB48-12_N	Width	47 7/8 "
Non combustible situation BGCV2-3048 / BGCV2-1248 Pro hood HCB48-12_N	Recommended Back Guards Ventilation	
Pro hood HCB48-12_N	Combustible situation	BGCV2-3048H
	Non combustible situation	BGCV2-3048 / BGCV2-1248
Safatu	Pro hood	HCB48-12_N
Salety	Safety	
ADA compliant	ADA compliant	•

Zones

Number of zones 6

SKU 82980

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

↓ ArchiCAD Gas Rangetop

Installation Guide EN

Guide d'installation FR

Planning Guide Professional Style Dial/Handle Accessories

↓ Rhino Gas Rangetop

SketchUp Gas Rangetop

User Guide EN

↓ User Guide FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com