

KM 3010 G Gas cooktop with 4 burners



- Simple controls -single-handed operation via rotary dial control
- Elegant design 24 3/4 (626) in (mm) wide gas on glass cooktop
- Versatile 4 burners
- Extremely safe GasStop function
- Easy cleaning ComfortClean dishwasher-safe grates

EAN: 4002515135051 / Material number: 09272050 / Old Material Number: 26301050USA

Heating type	
Fuel type	Gas
Construction type	
Independent of oven	•
Design	
Ceramic surface color	Black
Cast iron pot rests (matte black enameled)	•
Miele logo embossed in stainless steel	•
Ring features	
No. of rings	4
1st cooking zone/cooking area	
Position	front left
Type	High-speed burner
Max. rating in W	2700
2nd cooking zone/cooking area	
Position	rear left
Type	Economy burner
Max. rating in W	1000
3rd cooking zone/cooking area	1000
Position	rear right
Type	Standard burner
Max. rating in W	1700
	1700
4th cooking zone/cooking area Position	front right
	front right
Type	Standard burner
Max. rating in W	1700
Control panel	
Operation via knobs	
Electronic ignition with one-handed operation	•
Cleaning convenience	
Dishwasher-save trivets	•
Safety	
GasStop	
GasStop & ReStart	•
Technical data	
Dimensions (width) in in. (mm)	24 3/4 (626)
Dimensions (height) in in. (mm)	2 1/4 (54)
Built-in height with mains connection box in in. (mm)	2 1/2 (63)
Depth in in. (mm)	20 3/4 (526)
Cutout dimensions in mm (width) with surface-mounted	23 5/8 (600)
installation	
Cutout dimensions in mm (depth) with surface-mounted	19 3/4 (500)
installation	
Weight in lbs. (kg)	37 (17)
Total connected load in kW	7.20
Power cord length in in. (m)	3 (1.2)
Voltage in V	120
Frequency in Hz	60
Accessories supplied	
Number of mains cables with plug	No
1 3	



KM 3010 G Gas cooktop with 4 burners




EAN: 4002515135051 / Material number: 09272050 / Old Material Number: 26301050USA

Standard accessories

Jet set for liquid gas

Miele

KM 3010 G Gas cooktop with 4 burners



KM 3010 G (Installation drawing)

1. Front, 2. Casing depth, 3. Mains connection box with mains connection cable L = 2000 mmm, 4. Gas connection R 1/2" – ISO 7-1 (DIN EN 10226)