

# SINGLE-LOAD TOP-LOAD MATCHING DRYERS – 20 AMP


## MDE20PDUGW AND MDE20MNUGW



**COIN DROP READY**  
MDE20PDUGW pictured



**NON-VEND**  
MDE20MNUGW pictured



### TURBOVENT® SYSTEM\*

- A high-speed blower wheel optimizes performance in long vents
- High airflow helps reduce drying times for a wide variety of loads
- Helps to increase efficiency and turns over the life of the machine



### CONTROLS TO MEET YOUR NEEDS

- *Mechanical controls* provide a simple user interface with robust, easy-to-use knobs (MDE20MN)
- Get flexibility and individual cycle pricing options for optimal earnings through *Intelligent Controls with M-Series Technology*, while end users can easily choose their preferred wash experience with one-touch cycle selection (MDE20PD)
- USB port enables the import and export of cycle settings, audit data, and software updates (MDE20PD)



### LARGE CAPACITY

- 7.4 cu. ft. capacity dryer allows for large loads to be dried efficiently and effectively
- Delivers an optimal drying experience for users and helps maximize productivity



### BUILT TO LAST

- Porcelain enamel top — a durable finish that stands up to the demands of high traffic
- Full-wrap console — designed to help protect the internal components
- Front-panel accessibility — provides fast entry to internal components for streamlined self-service
- Extra-large reversible door — provides users unhindered access while loading and unloading

SINGLE-LOAD TOP-LOAD MATCHING DRYERS – 20 AMP	
PAYMENT CONFIGURATION	ELECTRIC
Coin Drop Ready	MDE20PDUGW
Non-Vend	MDE20MNUGW



\*On select models  
See [maytagcommerciallaundry.com](https://maytagcommerciallaundry.com) for warranty details.


VISIT [MAYTAGCOMMERCIALLAUNDRY.COM](https://MAYTAGCOMMERCIALLAUNDRY.COM) FOR MORE INFORMATION.

# SINGLE-LOAD TOP-LOAD MATCHING DRYERS – 20 AMP


## MDE20PDUGW AND MDE20MNUGW



### SIDE VIEW



### BACK VIEW



### MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number of 90° Turns		
	<b>Box Hood and Louvered Style</b>	<b>Angled Hood Style</b>
0	64 ft. (19.5 m)	58 ft. (17.7 m)
1	54 ft. (16.5 m)	48 ft. (14.6 m)
2	44 ft. (13.4 m)	38 ft. (11.6 m)
3	35 ft. (10.7 m)	29 ft. (8.8 m)
4	27 ft. (8.2 m)	21 ft. (6.4 m)



\*Includes height of metercase for coin drop and coin slide models  
 \*\*Use 4" (101.6 mm) diameter rigid aluminum or galvanized steel duct.  
 Never use plastic, non-metal, or combustible duct.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

MODELS	MDE20 (PD) MDE20 (MN)
COIN DROP READY NON-VEND	
<b>Fuel Type</b>	<b>Electric</b>
<b>CAPACITY</b>	
Cylinder Volume — cu. ft. (liters)	7.4 (210)
Cylinder Diameter — in. (mm)	26.26 (667)
Cylinder Depth — in. (mm)	23.2 (590)
<b>DIMENSIONS</b>	
Width — in. (mm)	27 (686)
Depth — in. (mm)	29.25 (743)
Height — in. (mm)	43 (1,092)*
Door Opening — in. (mm)	20.25 (514)
Exhaust Duct Diameter — in. (mm)	4 (101.6)**
<b>CRATED DIMENSIONS</b>	
Crated Width — in. (mm)	28.8 (731)
Crated Depth — in. (mm)	30.8 (782)
Crated Height — in. (mm)	44.65 (1,134)
<b>APPROXIMATE WEIGHT</b>	
Uncrated — lb (kg) Coin Drop & Coin Slide Models	125 (56.7)
Uncrated — lb (kg) Card Ready & Non-Vend Models	115 (52.2)
Crated — lb (kg) Coin Drop & Coin Slide Models	135 (61.2)
Crated — lb (kg) Card Ready & Non-Vend Models	125 (56.7)
<b>ELECTRICAL REQUIREMENTS</b>	
Voltage	220-230V
Breaker/Fuse — amps	20
Airflow — CFM (CMM)	215 (6.10)
Electric Heating Element (watts)	4,000
Motor Size — HP (kW)	1/3 (.25)

VISIT [MAYTAGCOMMERCIALLAUNDRY.COM](http://MAYTAGCOMMERCIALLAUNDRY.COM) FOR MORE INFORMATION.

®/™ © 2025 Maytag. All rights reserved.  
 MY250453 05/25