









Stainless Solid

Integrated Solid





Black Solid

White Solid

Key Features

- Refrigerator volume of 4.2 cu ft holds up to 61 bottles (12 oz) or 114 cans (12 oz)
- Digital touch pad control
- Refrigerator temperature range: 34°F 45°F
- Produces and stores up to 8 lbs of ice per day
- Crescent ice cube dimensions: 1/2" W x 3/4" H x 2 1/4" L
- White interior is illuminated with LED lighting
- Three removable tempered glass shelves

- No drain required
- Stainless steel handle (1/8" diameter)
- Integrated model requires 3/4" custom door panel and handle (not supplied by U-Line)
- Field reversible door is shipped right-hand hinged
- Built-in or freestanding
- Four adjustable leveling legs

Model Details


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHRI124-SS01A	115 / 60	Field Reversible	Stainless Solid	129 lb
UHRI124-IS01A	115 / 60	Field Reversible	Integrated Solid	126 lb
UHRI124-BS01A	115 / 60	Field Reversible	Black Solid	129 lb
UHRI124-WS01A	115 / 60	Field Reversible	White Solid	129 lb

Accessories


Model	Description	Finish	Shipping Weight
ULAFREESTANDB	Freestanding Kit	Black	3 lb
ULAWATERHOOKUP	Braided Water Supply Line Kit	N/A	2 lb


Front

Dimensions shown apply to all finishes, including Integrated (INT) models with $\frac{3}{4}$ " integrated panel/frame installed.



Side Top






Specifications

Model	HRI124	
Amps: Running	2.4	
Capacity: Refrigerator Volume (cu ft)	4.2	
Capacity: Bottle	61 (12oz)	
Capacity: Can	114 (12oz)	
Defrost Type	Frost Free	
Dimensions: Product Depth	22 ½" / 572 mm	
Dimensions: Product Height	34 ½" / 867 mm	
Dimensions: Product Width	23 ¹⁵ / ₁₆ " / 608 mm	
Energy Consumption: Avg. Per Year	575 kWh	
Ice Production Per Day	8 lb	
Ice Storage	8 lb	
Panel Height	30 ½" / 768 mm	
Panel Thickness	³ / ₄ " / 20 mm	
Panel Type	Solid Panel	
Panel Width	23 ³ / ₄ " / 603 mm	
Product Weight: Max	119 lb	
Refrigerant Type	R600a (1.34 oz)	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

4 ½" (108 mm) (165 mm) Water Line (70 mm) 3 ½" (95 mm)

Cabinet Cut-Out



Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details



Installation Notes

- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow



