QUICK REFERENCE GUIDE > RF135BRPX6 N Date: 21.10.2025 > 1

13.5 cu ft Series 5 Refrigerator Freezer


Series 5 | Contemporary

With generous storage and stylish stainless steel design with concealed handles for a more streamlined look.

- ActiveSmart[™] helps keep food fresher for longer
- Ultra flat door conceals handles for a streamlined look
- · Bottom freezer

DIMENSIONS

Height	67 3/4 "
Width	25 "
Depth	27 3/8 "



FEATURES & BENEFITS

Activesmart™ Foodcare

ActiveSmart™ Foodcare learns how you live. It's technology which understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Easy Cleaning

No more permanent dirty marks with our EZKleen feature for stainless steel refrigerators. Anti-fingerprint coating means you simply wipe clean any marks. Spill-safe secure glass shelves easily capture any drips or leaks.

Humidity Control

Your fruit and veges need different environments. The humidity control slides in each storage bin create a microclimate that helps keep food fresher for longer.

Design Quality

Our refrigerators are designed and built using quality materials. We use real stainless steel on our refrigerators and solid glass for shelving.

Clever Energy

Your refrigerator adapts to daily use by cooling and defrosting only when needed. This means your refrigerator uses the energy it needs without compromising on food care.

SPECIFICATIONS

Capacity

Total gross capacity	13.5 cu ft
Volume freezer	4 cu ft
Volume refrigerator	9.5 cu ft

Consumption

Energy rating	Energy Star
Energy usage	461kWh/year
In-use energy carbon emissions estimate	162.6kgCO2e/year

Features

Adjustable door shelves	7
Adjustable glass shelves	4
Covered door shelves	2
Door alarm	•
Front levelling feet	•
Fruit and vegetable bins	2
Full extension runners	•
LED lighting	•
Rear rollers	•

QUICK REFERENCE GUIDE > RF135BRPX6 N Date: 21.10.2025 > 2

Spill proof removable bins Stackable bottle holders 2 Freezer Features Bottle chill Fast freeze Large plastic bins Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage 10 A Supply requency Froduct Dimensions Depth Performance 27 3/8 " Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2 " Width 25 "	Smart appliance	
Freezer Features Bottle chill . Fast freeze . Large plastic bins . Performance ActiveSmart™ Foodcare . Adaptive defrost . Frost free . Sabbath mode . Power Requirements Rated current . Supply frequency . Supply voltage . Product Dimensions Depth . Height . Minimum air clearance at rear . Minimum air clearance each side . Minimum air clearance on top . 2 " **Total Company . **To	Spill proof removable bins	•
Bottle chill Fast freeze Large plastic bins Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth Performance 27 3/8 " Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 13/16 " Minimum air clearance on top 2 "	Stackable bottle holders	2
Bottle chill Fast freeze Large plastic bins Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth Performance 27 3/8 " Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 13/16 " Minimum air clearance on top 2 "		
Bottle chill Fast freeze Large plastic bins Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth Performance 27 3/8 " Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 13/16 " Minimum air clearance on top 2 "		
Fast freeze Large plastic bins Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth Height Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top Performance 1 ActiveSmart™ Foodcare 6 ActiveSmart™ Foodcare 6 ActiveSmart™ Foodcare 6 ActiveSmart™ Foodcare 6 ActiveSmart™ Foodcare 1 A A A A A ActiveSmart™ Foodcare 1 A A A A ActiveSmart™ Foodcare	Freezer Features	
Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top Performance 1 A March A 1 A March A 1 A March A Marc	Bottle chill	•
Performance ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage 10 A Supply voltage 115 V Product Dimensions Depth Height Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2 "	Fast freeze	•
ActiveSmart™ Foodcare Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage 10 A Supply voltage 115 V Product Dimensions Depth Peight 67 3/4 " Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2 "	Large plastic bins	•
Adaptive defrost Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage 10 A Supply voltage 115 V Product Dimensions Depth Peight For 3/4 " Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2 "	Performance	
Frost free Sabbath mode Power Requirements Rated current Supply frequency Supply voltage Product Dimensions Depth 127 3/8" Height 67 3/4" Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2"	ActiveSmart™ Foodcare	•
Power Requirements Rated current 10 A Supply frequency 60 Hz Supply voltage 115 V Product Dimensions Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Adaptive defrost	•
Power Requirements Rated current 10 A Supply frequency 60 Hz Supply voltage 115 V Product Dimensions Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Frost free	•
Rated current 10 A Supply frequency 60 Hz Supply voltage 115 V Product Dimensions Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Sabbath mode	•
Supply frequency Supply voltage Product Dimensions Depth Height 67 3/4 " Minimum air clearance at rear Minimum air clearance each side Minimum air clearance on top 2 "	Power Requirements	
Supply voltage 115 V Product Dimensions Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Rated current	10 A
Product Dimensions Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Supply frequency	60 Hz
Depth 27 3/8 " Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Supply voltage	115 V
Height 67 3/4 " Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Product Dimensions	
Minimum air clearance at rear 1 3/16 " Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Depth	27 3/8 "
Minimum air clearance each side 1 3/16 " Minimum air clearance on top 2 "	Height	67 3/4 "
Minimum air clearance on top 2 "	Minimum air clearance at rear	1 3/16 "
·	Minimum air clearance each side	1 3/16 "
Width 25 "	Minimum air clearance on top	2 "
	Width	25 "

Variable Temp Compartment

Bottle chill mode

SKU 26278

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

2D-DWG Freestanding Refrigerator Freezer

2D-DXF Freestanding Refrigerator Freezer

Data Sheet Freestanding Refrigerator Freezer

Energy Label

Water Filter Replacement Instructions - Parts 847200 and 847201 (English)

Installation Guide - Joiner Kit EN

J. Installation Guide EN

Water Filter Replacement Instructions - Parts 847200 and 847201 - FR

Installation Guide - Joiner Kit FR

Right To Repair Declaration (English, Canadian French)

↓ User Guide Refrigerator Freezer EN

↓ User Guide Refrigerator Freezer FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com