PRD366WHU

36-INCH DUAL-FUEL PRO HARMONY® RANGE

PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE












FEATURES & BENEFITS

- ★ Exclusive Star® Burner delivers superior flame spread for more even heating with QuickClean Base® designed for easy cleaning
- 2 ExtraLow® burners offer precision simmering, melting or keeping warm
 - Includes three Full Access® telescopic racks, all with an integrated easy-grip handle
- ★ Superfast 2-hour self-clean mode is the fastest in the industry
 - True Convection oven allows you to cook multiple dishes up to 5 levels of sheet pans with even baking results

TECHNICAL DETAILS			
Circuit Breaker	30 A		
Volts	240 / 208 V, 60Hz 4 Wire		
Energy Source	Gas and Electric		
Plug Type USA	No Plug		
Power Cord Length	Purchase Separately		
Gas Supply	3/4"		
WARRANTY			
Limited Warranty, Entire Appliance, Parts and Labor	2 Year		

SEE PAGE 2 FOR INCLUDED AND OPTIONAL ACCESSORIES

RANGETOP



Total number of cooktop Burners	6		
1 – Power of Back Left Burner BTU	15,000 and XLO		
2 – Power of Front Left Burner BTU	18,000 and XLO		
3 – Power of Back Center Burner BTU	15,000		
4 – Power of Front Center Burner BTU	18,000		
5 – Power of Back Right Burner BTU	15,000		
6 – Power of Front Right Burner BTU	18,000		

3	.,
OVEN	
Oven Capacity	4.9 cu. ft.

Cooking Modes

Bake, Convection Bake, True Convection, Convection Roast, Roast, Convection Broil, Broil

Sabbath	Yes		
Self Clean	Yes		
Telescopic Rack(s)	3		
Interior Lights	2		
Bake Power	2,000 W		
Broil Power	4,000 W		
Convection Power	2,750 W		
Home Connect® (Wi-Fi Enabled)	Yes		
Cavity Interior Dimensions (HxWxD)	16 3/8" x 28" 18 1/2"		
Cavity Usable Dimensions (HxWxD)	12" x 25 3/8" x 16 3/4"		

DIMENSIONS & WEIGHT	
Overall Appliance Dimensions (HxWxD)	35 3/4 " – 36 3/4 " × 35 15/16 " × 24 3/4 "
Required Cutout Size (HxWxD)	35 3/4 " – 36 3/4 " × 36" × 24"
Net Weight	410 lbs.

Page 1 of 5 3 / 23

PRD366WHU 36-INCH DUAL-FUEL PRO HARMONY® RANGE

PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE



ACCESSORIES (INCLUDED)

3 Telescopic Racks, Meat Probe, 1 Lg. Broil Pan, Island Trim

ACCESSORIES (OPTIONAL)



PWOKRINGHC

Wok Ring



PAGRIDDLE

Professional Griddle, Sits on Top of Grates Over 2 Star Burners, High-Release Coating



PARKB36HY

Metallic Blue Knob Kit



IV

High Altitude Kit, Natural Gas or Dual-Fuel Pro Harmony Ranges, 5,400 ft. to 10,200 ft.

Contact Customer Support

High Altitude Kit, Gas or Dual-Fuel Pro Harmony Ranges Connected to LP Gas, 10,000 ft. to 10,200 ft.



PA12CHPBLK

Chopping Block / Cutting Board



PA36WLBH

Pro Harmony 7" Low Backguard*



PALPKITHW

LP Conversion Kit, Pro Harmony Dual-Fuel Models with

Page 2 of 5 3 / 23


^{*}Models PCG305xx, PRD305xx, PRD606xx, PRG305xx, PRG305xx, PRG304xx and PRD304xx are suitable for 0" rear clearance to combustible surfaces. All other models: when using the included Island Trim a minimum 6" (152 mm) rear clearance is required to a combustible surface. When installing against a combustible surface, a Thermador® Low Backguard is required for a 0" rear clearance to the combustible surface. A Thermador Low Backguard must be purchased separately. A rear clearance to a surface covered in a noncombustible material (metal, ceramic tile, brick, marble, or stone) is 0" when using the included Island Trim. Clearances of less than 6" (152 mm) should be approved by the local codes and/or by the local authority having jurisdiction. Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA.

36-INCH DUAL-FUEL PRO HARMONY® RANGE






36-INCH RANGE DIMENSIONS



36-INCH RANGE CUTOUT DIMENSIONS



Range model	Gas zone A	Electric zone B	Х	С	D	E
All Harmony series	4'' (102)	6'' (152)	5'' (127)	N/A	N/A	2'' (51)
36''/ 48'' Grand series	4'' (102)	6'' (152)	8'' (203)	4'' (102)	3'' (76)	2'' (51)
60'' Grand series	4'' (102)	6'' (152)	8'' (203)	4'' (102)	3'' (76)	1'' (25)

Page 3 of 5 3 / 23

PRD366WHU


36-INCH DUAL-FUEL PRO HARMONY® RANGE

PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE



36-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "LOW BACK"

NOTE: A 36-inch minimum clearance is required between the top of the cooking surface and the bottom of an unprotected cabinet. A 30-inch clearance can be used when the bottom of the wood or metal cabinet is protected by not less than 1/4 inch of a flame retardant material covered with not less than No. 28 MSG sheet steel, 0.015 inch (0.4 mm) thick stainless steel, 0.024 inch (0.6 mm) aluminum, or 0.020 inch (0.5 mm) thick copper.



⚠ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition).

Clearances from non-combustible materials are not part of the ANSI Z21.1

scope and are not certified by CSA. Clearances of less than 6" (152 mm)


must be approved by the local codes and/or by the local authority having jurisdiction.

Page 4 of 5 3 / 23

PRD366WHU 36-INCH DUAL-FUEL PRO HARMONY® RANGE PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE



36-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "FLUSH ISLAND TRIM"



△ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition).

Clearances from non-combustible materials are not part of the ANSI Z21.1

scope and are not certified by CSA. Clearances of less than 6" (152 mm)

must be approved by the local codes and/or by the local authority having jurisdiction.

The control of the ANSI Z21.1

A scope and are not certified by CSA. Clearances of less than 6" (152 mm)

must be approved by the local codes and/or by the local authority having jurisdiction.

A scope and are not certified by CSA.

A scope and a

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

1 800 735 4328 | USA THERMADOR.COM | CANADA THERMADOR.CA | ©2023 BSH HOME APPLIANCES CORPORATION. ALL RIGHTS RESERVED.

Page 5 of 5 3 / 23