QUICK REFERENCE GUIDE > RHV3-484-N Date: 11.09.2025 > 1

48" Series 11 Professional 4 Burner + 4 Zone Hybrid Self-Cleaning Range, NG

Series 11 | Professional




With both induction and gas cooktops and two convection ovens, you're ready to create a feast - guided by an intuitive touchscreen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 23,500 BTU, for seriously fast boiling
- Four induction cooking zones, which can be paired to form two Smart Zones
- · 6.9 cu ft total oven capacity across two oven cavities

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 "



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

On the gas side of the cooktop, Sealed dual flow burners deliver power up to 23,500 BTU, while the induction side delivers up to 3700W. This finely tuned cooktop provides instant and immediate control from the highest heat to the most gentle simmer.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, high-quality glass, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function. The induction zones only need a quick wipe after use to keep them clean.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers

Branded coin end cap •

QUICK REFERENCE GUIDE > RHV3-484-N Date: 11.09.2025 > 2

Burner ratings		Sabbath mode	•	True convection	•
Maximum burner power	23500 BTU	Smart appliance	•	Warm	•
Power back left	18500BTU	Tilting touch screen interface	•		
Power back right	18500BTU				
Power front left	23500BTU			Oven features	
Power front right	18500BTU	Gas Requirements		Auto re-ignition system	•
Total cooktop power	79000 BTU	Fitting and pipe	½ NPT, min. %″ ∑ flex line	Concealed element	•
		Supply Pressure (natural gas)	6" to 9" W.C	Electronic oven control	•
		Supply Pressure (Hatural gas)	6 10 9 W.C	Full extension telescopic sliding shelves	•
Capacity				True convection	•
Shelf positions (main oven)	5	Main oven features			
Shelf positions (second oven)	5	Concealed Element	•	Oven functions	
Total capacity (main oven)	4.8 cu ft	Electronic oven control	•		
Total capacity second oven	2.1 cu ft	Full extension telescopic racks	•	Air fry	•
Usable capacity (main oven)	3.8 cu ft	Internal light	•	Bake	•
		True convection	•	Classic bake	•
				Clean	•
Cleaning				Convection bake	•
Easy clean porcelain basepan	•	Main oven functions		Convection Broil	•
Pyrolytic self-clean	•	Air fry	•	Dehydrate	•
		Bake	•	Maxi Broil	•
		Classic bake	•	Number of functions	15
Controls		Clean	•	Pastry bake	•
Dial with illuminated halo	•	Convection broil	•	Pizza bake	•
Dual control oven dials	•	Maxi broil	•	Rapid proof	•
Electric circuit	4 wire	Number of oven functions	15	Roast	•
High resolution display	•	Pizza bake	•	Slow cook	•
Metal illuminated dials	•	Rapid proof	•	True convection	•
Multi-language interface	•	Roast		Warm	•
Precise cooking with food probe	•	Self cleaning	•		
recipe And Food Based Functions	•	Slow cook	•	0	
		Slow Cook	•	Oven performance	

QUICK REFERENCE GUIDE > RHV3-484-N

Bake	4600 W	Left front zone rating	2100 (3700) W	Secondary oven functions		
Broil	3600 W	Left rear zone rating	2100 (3700) W	Air fry	•	
Broil power	4000 W	Number of cooking zones	4	Bake	•	
Main oven - True convection power	2500 W	PowerBoost	•	Classic bake	•	
		PowerBoost all zones	up to 3700 W	Convection bake	•	
		Right front zone rating	2100 (3700) W	Convection broil		
Power Requirements		Right rear zone rating	2100 (3700) W	Maxi broil	ě	
Connection	4-prong			Number of secondary oven functions	11	
	grounding type [NEMA 14-50P			Pastry bake	•	
	plug]	Recommended Back Guards Ventilation		Pizza bake	•	
Service	50 A	Combustible situation	BGRV3-3048H	Rapid proof		
Supply frequency	60 Hz	Non combustible situation	BGRV2-3048 /	Roast	•	
Supply voltage	208 - 240 V		BGRV2-1248	Warm		
Product Dimensions		Recommended hood	HCB48-12_N (48" Professional Range Hood, Dual Blower)			
Depth	29 1/8 "			SKU	82792	
Height	35 3/4 - 36 3/4 "	Safety				
Width	47 7/8 "	•		The much object of the property of the propert		
		ADA Compilant		product and model. Under our policy of continuous improve	nd specifications in this page apply to the specific our policy of continuous improvement, these	
		Pan detection system	•	dimensions and specifications may change at any time. You should therefore		
Rangetop features		Safety time out	•	check with Fisher & Paykel's Customer Care Centre to ensure correctly describes the model currently available. © Fisher &		
Gentle heat	•	Surface hot indicators	•	Appliances Ltd 2020		
Heat settings	9					
Induction cooking technology	•	Secondary oven features				
Sealed range top	•	Secondary over reactives		Other product downloads available at fisherpaykel.	.com	
SmartZone	2	3/4 Extension racks	2	A D DWG Dwd Fire LO . L W. D	SDV0 1040	
Vent trim included	•	_		2D-DWG Dual Fuel Cooker with Backguard BGRV2-1248 2D DWG Dual Fuel Cooker with Backguard BCDV2-7048		
Zone bridging	•	Food probe • Unterpal light • 2D-DWG Dual Fuel Cooker with Backguard Bo • 2D-DWG Dual Fuel Cooker with Backguard Bo • 2D-DWG Dual Fuel Cooker with Backguard Bo				
		Internal light	•	and Angled Trim	52 00 1011	

Rangetop Performance

 $\underline{\downarrow}$ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-1248

QUICK REFERENCE GUIDE > RHV3-484-N

- $\overline{\uparrow}$
- 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048
- 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ 2D-DXF Dual Fuel Range
- ↓ ArchiCAD Dual Fuel Range
- J. Installation Guide EN
- → Planning Guide Professional Style Dial/Handle Accessories
- ↓ Revit
- ↓ Rhino
- ↓ Right To Repair Declaration (English, French)
- ↓ SketchUp
- User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com