
### SPECIFICATION SHEET

# EPD61 SERIES RANGE HOOD



Especially designed to be installed outdoors in a covered patio or lanai area. For use over residential commercial-style cooking surfaces or gas and electric grills. This unit is not for use with a charcoal grill. A complete installation requires several optional components. Refer to page 2 when planning your installation.

#### **FEATURES**

- Professional outdoor design.
- 27-inch depth handles heat and size of outdoor grills (optional 3" wall extension to increase depth to 30").
- Brushed corrosion resistant 304 Stainless Steel.
- Four widths: 36, 42, 48, and 60 inches.
- Powerful, 1100 CFM internal blower tested to assure operation in corrosive environments.
- Bright halogen lighting (2 x 50 watts GU10 for 36-in. & 42-in. hoods, 3 x 50 watts GU10 for 48-in. & 60-in. hoods) (bulbs not included).
- 3-speed rotary control tested to assure operation in corrosive environments.
- 304 Stainless Steel baffle filters easily accessible and dishwasher-safe.
- Removable grease rail easy to clean.
- Heat Sentry<sup>TM</sup> detects excessive heat and adjusts blower speed automatically.
- UL and cUL listed for use in damp locations when properly connected to a GFCI circuit.





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

#### WALL EXTENSION (optional)

- Extends front of hood out an extra 3" (to 30") eliminates custom wall bump-outs.
- Stainless Steel construction matches range hood.
- Attaches to wall and back of range hood.

Model AWEPD36SS - 36-in. width Model AWEPD42SS - 42-in. width Model AWEPD48SS - 48-in. width Model AWEPD60SS - 60-in. width

#### **FLUE COVER (optional)**

- Stainless Steel construction matches range hood.
- Attaches to top of range hood shell.
- · Hides ducting and wipes clean easily.
- Extended depth available for hoods using the 3" wall extension.

Model AEEPD6SS - 6-in. high - for 8-ft. ceiling - standard depth Model AEEPD6SSE - 6-in. high - for 8-ft. ceiling - extended depth

Model AEEPD18SS - 18-in. high - for 9-ft. ceiling - standard depth Model AEEPD18SSE - 18-in. high - for 9-ft. ceiling - extended depth

Model AEEPD30SS - 30-in. high - for 10-ft. ceiling - standard depth Model AEEPD30SSE - 30-in. high - for 10-ft. ceiling - extended depth


Model AEEPD2445SS - collapsed height: 24" - maximum height 45" - standard depth

Model AEEPD2445SSE - collapsed height: 24" - maximum height 45" - extended depth

#### **SPECIFICATIONS**

VOLTS	HZ	AMPS	CFM	SONES	DUCT
120	60	9.0 MAX.	1160	11.0	10-in. ROUND

#### **AIR FLOW PERFORMANCE**



Broan-NuTone LLC Harford, Wisconsin www.broan-nutone.com 800-558-1711 Venmar Ventilation ULC Drummondville, Québec www.broan.ca 877-896-1119

REFERENCE	QTY.	REMARKS	Project	
			Location Architect Engineer Contractor	
			Submitted by	Date

## - EPD61 SERIES RANGE HOOD SYSTEM -

