

KM 2012 G
Gas cooktop
with a mono wok burner for special applications.




- Simple controls -single-handed operation via rotary dial control
- Professional design – 25 5/8 (650) in (mm) wide stainless steel trough
- Extremely safe – GasStop function
- Easy cleaning – ComfortClean dishwasher-safe grates

EAN: 4002516354093 / Material number: 11471350 / Old Material Number: 26201250USA

Design	
Cast iron pot rests (matte black enameled)	•
Stainless steel trough	•
1st cooking zone/cooking area	
Position	front left
Type	Single wok burner
Max. rating in W	3300
2nd cooking zone/cooking area	
Position	rear left
Type	Economy burner
Max. rating in W	1100
3rd cooking zone/cooking area	
Position	rear right
Type	Standard burner
Max. rating in W	1600
4th cooking zone/cooking area	
Position	front right
Type	Standard burner
Max. rating in W	1600
Safety	
GasStop	•
Technical data	
Dimensions (width) in in. (mm)	25 5/8 (650)
Dimensions (height) in in. (mm)	3 5/8 (90)
Depth in in. (mm)	20 1/2 (520)
Cutout dimensions in mm (width) with surface-mounted installation	22 1/8 (560)
Cutout dimensions in mm (depth) with surface-mounted installation	19 (480)
Weight in lbs. (kg)	30 (14)
Total connected load in kW	7.60
Power cord length in in. (m)	3 (1.2)
Voltage in V	120
Frequency in Hz	60
Accessories supplied	
Number of mains cables with plug	No

KM 2012 G
Gas cooktop
with a mono wok burner for special applications.



KM2010G (Installation drawing)

1. Front, 2. Building-in depth, 3. Gas connection R 1/2 - ISO 7-1 (DIN EN 10226), 4. Mains connection box with mains connection cable, L = 2000 mm