COMBINATION STACK DRYER/DRYER – 60 Hz

MLE/MLG26PDF MLE/MLG26PRF MLE/MLG26PRL MLE/MLG27PDF

MLG27PRF





COIN DROP EQUIPPED
MLE/MLG27PDF



CARD READER READY



LARGE CAPACITY

- Two 7.4 cu. ft. capacity dryers allow for large loads to be dried effectively
- Delivers an optimal drying experience for users and helps maximize productivity



CONTROLS TO MEET YOUR NEEDS

- An intuitive setup with easily programmable controls
- Allows owners to take control of their revenue streams with time-of-day pricing and additional costs for end-user upgrades
- Simple, one-touch cycle selection provides clear options for end users
- USB port enables the import and export of cycle settings, audit data, and software updates



FRONT-ACCESS PANEL

- Streamlines self-service by providing quick entry to the motor, transmission, and wash tub
- Minimizes downtime to help keep the machine running



BUILT TO LAST

- Porcelain enamel top a durable finish that stands up to the demands of high traffic
- Front-panel accessibility provides fast entry to internal components for streamlined self-service
- Blower guard reduces service calls, helping to keep machines running at optimal turns

SINGLE-LOAD STACK DRYER/DRYER — 60 Hz					
PAYMENT CONFIGURATION	GAS	ELECTRIÇ	ELECTRIC (CANADA)		
Coin Drop Equipped	MLG26PDFWW MLG27PDFWW	MLE26PDFYW MLE27PDFYW	MLE27PDFZW		
Card Reader Ready	MLG26PRFWW MLG26PRLWW MLG27PRFWW	MLE26PRFYW MLE26PRLYW	MLE26PRFZW		





See maytagcommerciallaundry.com for warranty details.


COMBINATION STACK DRYER/DRYER - 60 Hz


MLE/MLG26PDF MLE/MLG26PRF

MLE/MLG26PRL MLE/MLG27PDF

MLG27PRF

SIDE VIEW





MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number of 90° Turns	Rigid Mo	etal Vent
	Box Hood and Louvered Style	Angled Hood Style
0	130 ft. (39.6 m)	129 ft. (39.3 m)
1	125 ft. (38.1 m)	119 ft. (36.3 m)
2	115 ft. (35.1 m)	109 ft. (33.2 m)
3	106 ft. (32.3 m)	100 ft. (30.5 m)
4	98 ft. (29.9 m)	92 ft. (28.0 m)

Maximum length of vent system depends upon the type of vent used, number of elbows, and type of exhaust hood. For vent systems not covered by the vent specification chart, see your parts distributor.

MODELS	MLE26 (PD/PR) MLE27 (PD)	MLG26 (PD/PR) MLG27 (PD)	MLE26 (PR) MLE27 (PD)		
FUEL TYPE	Electric	Gas	Electric (Canada)		
CAPACITY					
Cylinder Volume — cu. ft. (liters)	7.4 (209.5)	7.4 (209.5)	7.4 (209.5)		
Cylinder Diameter — in. (mm)	26.26 (667)	26.26 (667)	26.26 (667)		
Cylinder Depth — in. (mm)	23.2 (590)	23.2 (590)	23.2 (590)		
DIMENSIONS					
Width — in. (mm)	27 (686)	27 (686)	27 (686)		
Depth — in. (mm)	29 (737)	29 (737)	29 (737)		
Height — in. (mm) PR models	74.25 (1,886)	74.25 (1,886)	74.25 (1,886)		
Height — in. (mm) PD models	76.75 (1,950)	76.75 (1,950)	76.75 (1,950)		
Door Opening — in. (mm)	20.25 (514)	20.25 (514)	20.25 (514)		
Exhaust Duct Diameter — in. (mm)	4 (101.6)*	4 (101.6)*	4 (101.6)*		
CRATED DIMENSIONS					
Crated Width — in. (mm)	28.7 (730)	28.7 (730)	28.7 (730)		
Crated Depth — in. (mm)	33.4 (848)	33.4 (848)	33.4 (848)		
Crated Height — in. (mm)	79.1 (2008)	79.1 (2008)	79.1 (2008)		
APPROXIMATE WEIGHT					
Uncrated — lb (kg) Coin Drop Models	272 (123.4)	275 (124.7)	275 (124.7)		
Uncrated — lb (kg) Card Ready & Non-Vend Models	250 (113.4)	250 (113.4)	250 (113.4)		
Crated — lb (kg) Coin Drop Models	294 (133.4)	294 (133.4)	294 (133.4)		
Crated — lb (kg) Card Ready & Non-Vend Models	275 (124.7)	275 (124.7)	275 (124.7)		
ELECTRICAL REQUIREMENTS					
Voltage	240V – 60Hz	120V – 60Hz	240V – 60Hz		
Breaker/Fuse — amps	30	15	30		
Airflow — CFM (CMM)	200 (5.7)	215 (6.1)	215 (6.1)		
Electric Heating Element (watts)	5,600	N/A	5,250		
Gas Rating — BTU/hr (kcal/hr)	N/A	22,000 (5,544)	N/A		
Gas Inlet Size — in.	N/A	3/8 N.P.T.	N/A		
Motor Size — HP (kW)	1/3 (.25)	1/3 (.25)	1/3 (.25)		





*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.
See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice. Export model ships without coin-drop mechanism.