



ASDR1524PNR



32" x 14.75" x 17.88" (H x W x D)

15" wide shallow depth built-in undercounter ADA compliant 2-drawer refrigerator with panel-ready stainless steel drawer fronts and black cabinet

Highlights:

Panel-ready drawers allow you to customize the look to match existing cabinetry

Uniquely shallow depth under 18" for an easy fit in kitchen islands

32" height for use under lower ADA compliant counters

Product Features:

2-Drawer All-Refrigerator	15" wide 1.7 cu.ft. all-refrigerator with two gliding drawers
Panel-ready drawer fronts	Drawers can be customized with overlay panels sized (at 14.75" W x 14.1" H at 3/4" thick) to match or accent existing cabinetry
Stainless steel front finish	Fully finished drawer fronts also allows you to choose a traditional stainless steel front if not installing overlay panels
Less than 18" deep	Unique 17.88" shallow depth is ideal for wet bars, island kitchens, and other undercounter areas with limited footprint space
ADA compliant design	Sized just under 32" high to allow installation under lower ADA compliant counters
Adjustable height	Leveling legs can be extended up to 2", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34" if used under more standard sized cabinets
Built-in capable	Front-breathing design allows you to make the best use of space by installing your appliance under the counter and flush with other cabinets in 15" wide openings
Stainless steel drawers	Drawer interiors and exteriors are fully constructed from 304 grade stainless steel for lasting durability with a finished front for an elegant look
Professional handles	Stainless steel handles add style to any setting



ASDR1524PNR Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Nominal Width	15.0" (38 cm)
Width	14.75" (37 cm)
Nominal Depth	18.0" (46 cm)
Depth	17.88" (45 cm)
Depth with door at 90°	29.63" (75 cm)
Capacity	1.7 cu.ft. (48 L)
Defrost Type	Frost-Free
Door	Stainless Steel/Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	235.0kWh/year
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	65.0 lbs. (29 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101088921
Refrigerator Features	
Sabbath Mode	Yes
Door Swing	Drawer
Height Adjustable	Yes
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	0.64oz.
High Side PSI	270.0
Low Side PSI	105.0
Level Legs Qty	4
Interior Light	Yes
Interior Drawers	Yes
Interior Drawers Qty	2

Temperature Range	36 to 43°F
Sound Level	32.9 dB
Drawer Dimensions	
Interior Height 1	8.0" (20 cm)
Interior Width 1	9.0" (23 cm)
Interior Depth 1	11.25" (29 cm)
Interior Height 2	8.0" (20 cm)
Interior Width 2	9.0" (23 cm)
Interior Depth 2	11.25" (29 cm)
Dimensions	
Compressor Step Height	3.75" (10 cm)
Compressor Step Width	9.0" (23 cm)
Compressor Step Depth	4.75" (12 cm)

