


PERFORMANCE DATA SHEET

Model: PureSource Ultra® II-U Using Replacement Cartridge EPTWFOU1™

APPLICATION GUIDELINES / CONDITIONS OF USE	
Water Supply	Potable Water
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C)
Water Pressure	30 - 100 psi (206.8 - 689.5 kPa)
Service Flow	0.65 gpm maximum (2.46 lpm)
<ul style="list-style-type: none"> It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information. While testing was performed under standard laboratory conditions, actual performance may vary. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401. The compounds certified under NSF 401 have been deemed as "emerging compounds/incidental contaminants. Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality. 	

REPLACEMENT CARTRIDGE INFORMATION	
Replacement Element: EPTWFOU1™. For estimated cost of replacement elements please call 1-800-374-4432 or visit us on the web at frigidaire.com	
PERFORMANCE DATA	
MODEL: PureSource Ultra-U. Use the replacement cartridge EPTWFOU1™.	
	System tested and certified by NSF International against NSF/ANSI Standard 42, Standard 53, and Standard 401 for the reduction of substances listed below.
SYSTEM SPECIFICATIONS	
Capacity	200 gallons (757 liters)

WARNING

Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.
Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system.
Your Water Filtration system will withstand up to 100 lbs/in² (psi) water pressure.

To reduce the risk associated with choking:
DO NOT allow children under 3 years of age to have access to small parts during the installation of this product.

To reduce the risk associated with the ingestion of contaminants:
DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after use of the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

CAUTION

To reduce the risk associated with property damage due to water leakage or flooding:

- Read and follow Use Instructions before installation and use of this system.
- Change the disposable filter cartridge at the recommended interval; the disposable filter cartridge MUST be replaced every 6 months or sooner.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.
- Installation and use MUST comply with all state and local plumbing codes.
- Protect from freezing, remove filter cartridge when temperatures are expected to drop below 33° F (4.4°C).
- DO NOT install systems in areas where ambient temperatures may go above 110° F (43.3°C).
- DO NOT install on hot water supply lines. The maximum operating water temperature of this filter system is 100°F (37.8°C).

Substance Reduction	Average Influent	NSF/ANSI Specified Challenge Concentration	Average % Reduction/ Minimum Reduction	Average Product Water Concentration	Maximum Permissible Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine	2.0 mg/L	2.0 mg/L ± 10%	>97.4 / 97.4%	0.05 mg/L	N/A	≥ 50%	J-00297278
Nominal Particulate Class I	4,600,000 pts/mL	At least 10,000 particles/mL	99.3 / 99.0%	38,000 pts/ml	N/A	≥85%	J-00297279
Asbestos	290 MFL	10 to 100 MFL; fibers greater than 10 µm in length	>99 / >99%	< 1MLF	N/A	≥99%	J-00297237
Atrazine	8.8 ug/L	9 ug/L ± 10%	>94.3 / 94.3%	0.0005 mg/L	5 ug/L	N/A	J-00297270
Benzene	14 ug/L	15 ug/L ± 10%	>96.5 / 96.5%	0.0005 mg/L	0.005 mg/L	N/A	J-00297271
Carbofuran	80 ug/L	80 ug/L ± 10%	>98.8 / 98.8%	0.001 mg/L	40 ug/L	N/A	J-00297273
Cysts*	140,000 cycst/L	Minimum 50,000 cysts/L	>99.99 / 99.99%	<1 cyst/L	N/A	≥99.95%	J-00297235
Endrin	5.7 ug/L	6 ug/L ± 10%	96.4 / 94.8%	0.2 ug/L	2 ug/L	N/A	J-00297646
Lead pH 6.5	150 ug/L	150 ug/L ± 10%	99.6 / 99.3%	0.0005 mg/L	10 ug/L	N/A	J-00297265
Lead pH 8.5	150 ug/L	150 ug/L ± 10%	>99.7 / >99.7%	0.0005 mg/L	10 u/L	N/A	J-00297266
Lindane	2.0 ug/L	2 ug/L ± 10%	>99.0 / 98.9%	0.02 ug/L	0.2 ug/L	N/A	J-00297274
Mercury @ pH 6.5	5.5 ug/L	6 ug/L ± 10%	96.3 / 96.3%	0.2 ug/L	2 ug/L	N/A	J-00297268
Mercury @ pH 8.5	5.7 ug/L	6 ug/L ± 10%	94.5 / 89.5%	0.3 ug/L	2 ug/L	N/A	J-00297267
O-Dichlorobenzene	1800 ug/L	1800 ug/L ±10%	>99.9 / 99.9%	0.0005 mg/L	600 ug/L	N/A	J-00297647
P-Dichlorobenzene	200 ug/L	225 ug/L ± 10%	>99.7 / 99.8%	0.5 ug/L	75 ug/L	N/A	J-00297651
Tetrachloroethylene	14 ug/L	15 ug/L ± 10%	>96.4 / 95.8%	0.0005 mg/L	5 ug/L	N/A	J-00297648
Toxaphene (Pesticide)	15 ug/L	15 ug/L ± 10%	>93.2 / 93.1%	0.001 mg/L	3 ug/L	N/A	J-00297649
2,4-D (Herbicide)	220 ug/L	210 ug/L ± 10%	99.3 / 97.4%	1.6 ug/L	70 ug/L	N/A	J-00297645
Atenolol	220 ug/L	200 ng/L ± 20%	>95.5 / 95.5%	10 ng/L	30 ng/L	N/A	J-00297275
Bisphenol A	2200 ng/L	2000 ng/L ± 20%	>99.1 / 99.1%	20 ng/L	300 ng/L	N/A	J-00297276
Estrone	140 ng/L	140 ng/L ± 20%	>96.6 / 96.4%	5 ng/L	20 ng/L	N/A	J-00297276
Ibuprofen (Pharma)	440 ng/L	400 ng/L ± 20%	>95.5 / 95.3%	20 ng/L	60 ng/L	N/A	J-00297276
Naproxen	160 ng/L	140 ng/L ± 20%	>96.8 / 96.7%	5 ng/L	20 ng/L	N/A	J-00297276
Nonylphenol	1500 ng/L	1400 ng/L ± 20%	>96.7 / 96.6%	50 ng/L	200 ng/L	N/A	J-00297276
Phenytoin	220 ng/L	200 ng/L ± 20%	>95.5 / 95.5%	10 ng/L	30 ng/L	N/A	J-00297276
Trimethoprim	140 ng/L	140 ng/L ± 20%	>96.6 / 96.5%	5 ng/L	20 ng/L	N/A	J-00297275

Contaminant reduction determined by NSF testing.

* Based on the use of Cryptosporidium parvum oocysts

FRIGIDAIRE

10200 David Taylor Drive, Charlotte, NC 28262, 2008 ELECTROLUX HOME PRODUCTS, INC. 1-800-374-4432


NSF is a trademark of NSF International.

P/N: A02536407

PERFORMANCE DATA SHEET

Model: PureSource Ultra® II-M Using Replacement Cartridge EPTWFO1™

APPLICATION GUIDELINES / CONDITIONS OF USE	
Water Supply	Potable Water
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C)
Water Pressure	30 - 100 psi (206.8 - 689.5 kPa)
Service Flow	0.65 gpm maximum (2.46 lpm)
<ul style="list-style-type: none"> It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information. While testing was performed under standard laboratory conditions, actual performance may vary. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401. The compounds certified under NSF 401 have been deemed as emerging compounds/incidental contaminants. Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality. 	

REPLACEMENT CARTRIDGE INFORMATION	
Replacement Element: EPTWFO1™. For estimated cost of replacement elements please call 1-800-374-4432 or visit us on the web at frigidaire.com.	
PERFORMANCE DATA	
MODEL: PureSource Ultra® II. Use the replacement cartridge EPTWFO1™.	
	System tested and certified by NSF International against NSF/ANSI Standard 42, Standard 53, and Standard 401 for the reduction of substances listed below.
SYSTEM SPECIFICATIONS	
Capacity	125 gallons (473 liters)

WARNING

Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage. Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system. Your Water Filtration system will withstand up to 100 lbs/in² (psi) water pressure.

To reduce the risk associated with choking:
DO NOT allow children under 3 years of age to have access to small parts during the installation of this product.

To reduce the risk associated with the ingestion of contaminants:
DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after use of the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

CAUTION

To reduce the risk associated with property damage due to water leakage or flooding:

- Read and follow the Use and Care Guide before installation and use of this system.
- Change the disposable filter cartridge at the recommended interval; You MUST replace the disposable filter cartridge every 6 months or sooner.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.
- Installation and use MUST comply with all state and local plumbing codes.
- Protect from freezing, remove filter cartridge when temperatures are expected to drop below 33°F (4.4°C).
- DO NOT install systems in areas where ambient temperatures may go above 110°F (43.3°C).
- DO NOT install on hot water supply lines. The maximum operating water temperature of this filter system is 100°F (37.8°C).

Substance Reduction	Average Influent	NSF/ANSI Specified Challenge Concentration	Average % Reduction/ Minimum Reduction	Average Product Water Concentration	Maximum Permissible Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine	2.0 mg/L	2.0 mg/L ± 10%	>97.4 / 97.4%	0.05 mg/L	N/A	≥ 50%	J-00297278
Nominal Particulate Class I	4,600,000 pts/mL	At least 10,000 particles/mL	99.3 / 99.0%	38,000 pts/ml	N/A	≥85%	J-00297279
Asbestos	290 MFL	10 to 100 MFL; fibers greater than 10 µm in length	>99 / >99%	< 1MLF	N/A	≥99%	J-00297237
Atrazine	8.8 ug/L	9 ug/L ± 10%	>94.3 / 94.3%	0.5 ug/L	3 ug/L	N/A	J-00297270
Benzene	14 ug/L	15 ug/L ± 10%	>96.5 / 96.5%	0.5 ug/L	5 ug/L	N/A	J-00297271
Carbofuran	80 ug/L	80 ug/L ± 10%	>98.8 / 98.8%	1 ug/L	40 ug/L	N/A	J-00297273
Cysts*	140,000 cycst/L	Minimum 50,000 cysts/L	>99.99 / 99.99%	<1 cyst/L	N/A	≥99.95%	J-00297235
Endrin	5.7 ug/L	6 ug/L ± 10%	96.4 / 94.8%	0.2 ug/L	2 ug/L	N/A	J-00297646
Lead pH 6.5	150 ug/l	150 ug/L ± 10%	99.6 / 99.3%	0.5 ug/L	10 ug/L	N/A	J-00297265
Lead pH 8.5	150 ug/l	150 ug/L ± 10%	>99.7 / >99.7%	0.5 ug/L	10 ug/L	N/A	J-00297266
Lindane	2.0 ug/L	2 ug/L ± 10%	>99.0 / 98.9%	0.02 ug/L	0.2 ug/L	N/A	J-00297274
Mercury pH 6.5	5.5 ug/L	6 ug/L ± 10%	96.3 / 96.3%	0.2 ug/L	2 ug/L	N/A	J-00297268
Mercury pH 8.5	5.7 ug/L	6 ug/L ± 10%	94.5 / 89.5%	0.3 ug/L	2 ug/L	N/A	J-00297267
O-Dichlorobenzene	1800 ug/L	1800 ug/L ±10%	>99.9 / 99.9%	0.5 ug/L	600 ug/L	N/A	J-00297647
P-Dichlorobenzene	200 ug/l	225 ug/L ± 10%	>99.7 / 99.8%	0.5 ug/L	75 ug/L	N/A	J-00297651
Tetrachloroethylene	14 ug/L	15 ug/L ± 10%	>96.4 / 95.8%	0.5 ug/L	5 ug/L	N/A	J-00297648
Toxaphene (Pesticide)	15 ug/L	15 ug/L ± 10%	>93.2 / 93.1%	1 ug/L	3 ug/L	N/A	J-00297649
2,4-D (Herbicide)	220 ug/L	210 ug/L ± 10%	99.3 / 97.4%	1.6 ug/L	70 ug/L	N/A	J-00297645
Atenolol	220 ug/L	200 ng/L ± 20%	>95.5 / 95.5%	10 ng/L	30 ng/L	N/A	J-00297275
Bisphenol A	2200 ng/L	2000 ng/L ± 20%	>99.1 / 99.1%	20 ng/L	300 ng/L	N/A	J-00297276
Estrone	140 ng/L	140 ng/L ± 20%	>96.6 / 96.4%	5 ng/L	20 ng/L	N/A	J-00297276
Ibuprofen (Pharma)	440 ng/L	400 ng/L ± 20%	>95.5 / 95.3%	20 ng/L	60 ng/L	N/A	J-00297276
Naproxen	160 ng/L	140 ng/L ± 20%	>96.8 / 96.7%	5 ng/L	20 ng/L	N/A	J-00297276
Nonylphenol	1500 ng/L	1400 ng/L ± 20%	>96.7 / 96.6%	50 ng/L	200 ng/L	N/A	J-00297276
Phenytoin	220 ng/L	200 ng/L ± 20%	>95.5 / 95.5%	10 ng/L	30 ng/L	N/A	J-00297276
Trimethoprim	140 ng/L	140 ng/L ± 20%	>96.6 / 96.5%	5 ng/L	20 ng/L	N/A	J-00297275

Contaminant reduction determined by NSF testing.

* Based on the use of Cryptosporidium parvum oocysts

FRIGIDAIRE

10200 David Taylor Drive, Charlotte, NC 28262, 2008 ELECTROLUX HOME PRODUCTS, INC. 1-800-374-4432

NSF is a trademark of NSF International.



This filter is certified by the Water Quality Association to
WGA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément
à la norme WGA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según
WGA/ASPE/ANSI-803 por sostenibilidad.