

SINGLE-LOAD TOP-LOAD WASHERS – 60 Hz

MAT23



COIN DROP EQUIPPED
MAT23PDAWW (pictured)



CANADA COIN DROP EQUIPPED
MAT23PDAXW (pictured)



CARD READER READY
MAT23PRAWW (pictured)



COIN SLIDE READY
MAT23CSAWW (pictured)



NON-VEND
MAT23MNAWW (pictured)

AMERICA
AN AMERICAN COMPANY FOR OVER 100 YEARS



DEEP-WATER WASH SYSTEM

- Provides optimal wash performance with deep-water wash and rinse cycle options and vigorous cleaning action
- Traditional flex-vane agitator provides four distinct wash profiles — from aggressive to gentle — designed to pull clothes from the top to the bottom of the wash basket
- PowerWash® cycle provides more agitation, hotter water, and an extra rinse for the dirtiest loads



TRADITIONAL FLEX-VANE AGITATOR

- Powered by a ½ hp PSC motor and fin design
- Alternates between four distinct wash patterns — from aggressive to gentle
- Generates outstanding clothes movement and extensive deep-cleaning action to tackle a variety of loads



CONTROLS TO MEET YOUR NEEDS

- *Mechanical controls* provide a simple user interface with robust, easy-to-use knobs (MAT23CS and MAT23MN)
- Get flexibility and individual cycle pricing options for optimal earnings through *Intelligent Controls with M-Series Technology*, while end users can easily choose their preferred wash experience with one-touch cycle selection (MAT23PD and MAT23PR)



BUILT TO LAST

- Heavy-duty front panel — robust and easy to remove
- Front-panel accessibility — provides fast entry to the motor, transmission, and wash tub for streamlined self-service
- Built-in, easy-to-use diagnostics — help servicers identify problems quickly
- Watertight, flexible, triple-lip seal — helps keep moisture safely away from the shaft and protects the premium bearings

SINGLE-LOAD TOP-LOAD WASHER MODELS — 60 Hz

| PAYMENT CONFIGURATION | MODEL NUMBER |
|------------------------------|--------------------------------|
| Coin Drop Equipped | MAT23PDAWW MAT23PDAXW - CAN |
| Card Reader Ready / Non-Vend | MAT23PRAWW |
| Coin Slide Ready | MAT23CSAWW |
| Non-Vend | MAT23MNAWW |

See maytagcommerciallaundry.com for warranty details.

VISIT MAYTAGCOMMERCIALLAUNDRY.COM FOR MORE INFORMATION.


®/™ © 2024 Maytag. All rights reserved.
MY230290 04/24

SINGLE-LOAD TOP-LOAD WASHERS – 60 Hz


MAT23




FRONT VIEW



SIDE VIEW



BACK VIEW



*Includes height of metercase.

**Based on 2018 United States DOE J2 Testing with factory preset cycles.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

| MODELS | MAT23 (PD) | MAT23 (PR) | MAT23 (CS) | MAT23 (MN) |
|---|--------------------|------------------------------|------------------|----------------|
| PAYMENT CONFIGURATION | COIN DROP EQUIPPED | CARD READER READY / NON-VEND | COIN SLIDE READY | NON-VEND |
| DIMENSIONS | | | | |
| Depth — in. (mm) | 26 (660) | 26 (660) | 26 (660) | 26 (660) |
| Width — in. (mm) | 27 (686) | 27 (686) | 27 (686) | 27 (686) |
| Height — in. (mm) | 44.5 (1,130)* | 42.5 (1,080) | 44.5 (1,130)* | 42.5 (1,080) |
| Lid Opening — in. (mm) | 17 (432) | 17 (432) | 17 (432) | 17 (432) |
| CRATED DIMENSIONS | | | | |
| Crated Width — in. (mm) | 29 (737) | 29 (737) | 29 (737) | 29 (737) |
| Crated Depth — in. (mm) | 27.52 (699) | 27.5 (699) | 27.5 (699) | 27.5 (699) |
| Crated Height — in. (mm) | 49 (1,255) | 49 (1,255) | 49 (1,255) | 49 (1,255) |
| APPROXIMATE WEIGHT | | | | |
| Uncrated — lb (kg) | 159 (72.1) | 146 (66.2) | 156 (70.8) | 145 (65.8) |
| Crated — lb (kg) | 177 (80.3) | 164 (74.4) | 174 (78.9) | 163 (73.9) |
| ELECTRICAL REQUIREMENTS | | | | |
| Voltage | 120V | 120V | 120V | 120V |
| Breaker/Fuse — Amps | 15 | 15 | 15 | 15 |
| WATER INLET HOSE/DRAIN HOSE | | | | |
| Operating Pressure — psi (bar) | 20–100 (1-8) | 20–100 (1-8) | 20–100 (1-8) | 20–100 (1-8) |
| Inlet Hose Length — ft (m) | 6 (1.8) | 6 (1.8) | 6 (1.8) | 6 (1.8) |
| Drain Hose Length — ft (m) | 4 (1.3) | 4 (1.3) | 4 (1.3) | 4 (1.3) |
| APPROXIMATE WATER USAGE | | | | |
| Average Total Water Usage Per Cycle — gallons (liters) | 17.06 (64.6)** | 17.06 (64.6)** | 23.95 (90.7)** | 23.95 (90.7)** |
| Average Hot Water Usage Warm Water Cycle — gallons (liters) | 0.56 (2.1) | 0.56 (2.1) | 1.13 (4.2) | 1.13 (4.2) |
| Average Hot Water Usage Hot Water Cycle — gallons (liters) | 6.34 (23.99) | 6.34 (23.99) | 6.62 (25.06) | 6.62 (25.06) |
| Extract Speed — Max G-Force/Max RPM | 144 / 700 | 144 / 700 | 144 / 700 | 144 / 700 |
| Motor Size — hp (kW) | .5 (.37) | .5 (.37) | .5 (.37) | .5 (.37) |
| Water Factor | 5.11 | 5.11 | 7.17 | 7.17 |
| Modified Energy Factor | 1.71 | 1.71 | 1.64 | 1.64 |