## SUMMIT

# SBC15NKIF



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed kegerator, auto defrost with digital thermostat, panel-ready door, front lock, sealed back, and black cabinet

### **Highlights:**

Designed for built-in installation under the counter

Listed to NSF-7 standards and meets UL 471 for commercial use

15" wide design makes it ideal for smaller residential and commercial settings

#### **Product Features:**

15" wide design	Slim-fit design complements smaller commercial and residential spaces	
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Built-in capability	Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra ¼" of space due to the door design. For more information, see the user manual	
Versatile kegerator	2.9 cu.ft. interior can accept a 1/6 (sixtel) barrel keg or a pony keg; compatible with beer, wine, coffee, or kombucha tap systems	
Panel-ready door	Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Tap cool system	Keeps cold air flowing to the tower for consistently cold beer	
Stainless steel floor cover	Interior includes steel cover to protect the floor when loading kegs	
-		



### **SBC15NKIF Specifications:**

Height of Cabinet 34.25" (87 cm)  Width 15.0" (38 cm)  Width with Door Open 15.25" (39 cm)  Depth 22.5" (57 cm)  Depth with Handle 24.5" (62 cm)  Depth with door at 90° 36.5" (93 cm)  Capacity 2.9 cu.ft. (82 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Width with Door Open  Depth  Depth  22.5" (57 cm)  Depth with Handle  24.5" (62 cm)  Depth with door at 90°  Capacity  2.9 cu.ft. (82 L)  Defrost Type  Automatic  Door  Panel-Ready  Cabinet  US Electrical Safety  ETL  Canadian Electrical  Safety  Sanitation  ETL-S  Energy Usage/Year  22.5" (39 cm)  24.5" (62 cm)  Advantage  Panel-Ready  ETL-C  Safety  ETL-C  Safety  Sanitation  ETL-S		
Depth 22.5" (57 cm)  Depth with Handle 24.5" (62 cm)  Depth with door at 90° 36.5" (93 cm)  Capacity 2.9 cu.ft. (82 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Depth with Handle 24.5" (62 cm)  Depth with door at 90° 36.5" (93 cm)  Capacity 2.9 cu.ft. (82 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Depth with door at 90° 36.5" (93 cm)  Capacity 2.9 cu.ft. (82 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Capacity 2.9 cu.ft. (82 L)  Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Defrost Type Automatic  Door Panel-Ready  Cabinet Black  US Electrical Safety ETL  Canadian Electrical Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
DoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year280.0kWh/year		
Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 280.0kWh/year		
US Electrical Safety ETL  Canadian Electrical ETL-C Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Canadian Electrical ETL-C Safety  Sanitation ETL-S  Energy Usage/Year 280.0kWh/year		
Sanitation ETL-S Energy Usage/Year 280.0kWh/year		
Energy Usage/Year 280.0kWh/year		
A		
Amps 1.25		
Voltage/Frequency 115 V AC/60 Hz		
Weight 74.0 lbs. (34 kg)		
Shipping Weight 80.0 lbs. (36 kg)		
Estimated Time to Ship 3 to 5 days		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Years		
Kegerator		
Door Swing RHD		
Reversible Factory Reversible		
Adjustable Shelves Yes		
Shelf Type Chrome		
Shelf Qty 2		
Thermostat Type Digital		
Fan Type Exterior		
Refrigerant R600a		
Refrigerant Amount 1.06 oz.		
High Side PSI 150.0		
Low Side PSI 50.0		
Inter Height 26.75" (68 cm)		
Interior Width 11.75" (30 cm)		
Interior Depth 17.5" (44 cm)		
Compressor Step Height 3.75" (10 cm)		

Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	5.0" (13 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	34° to 50° F



