

## PDR 908 HP [EL]

Professional heat-pump dryer, Little Giants

With very low energy consumption and short program runtimes. Load capacity 18 (8.0) lb (kg).



- Drum volume 4.59 (130.00) ft<sup>3</sup> (l) 4.59 (130.00) ft<sup>3</sup> (l), load capacity 18 (8.0) lb (kg)
- Tested for intensive use – unique Miele quality
- Top convenience with full-touch color display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof networking via WiFi

EAN: 4002516195917 / Material number: 11204480 / Old Material Number: 52908159NAM

| Construction type and design  |                              |
|---|------------------------------|
| Front   | Lotos white, enamelled       |
| Fascia color  | Edelstahl                    |
| Load in lbs.(kg)  | 18 (8.0)                     |
| Drum volume in gal(l)   | 4.59 (130.00)                |
| Drying system   | Heat pump                    |
| Door opening [Ø] in in.(mm)   | 14 5/8 (370)                 |
| Door opening angle in degrees   | 167                          |
| Door hinging  | left                         |
| Stainless steel honeycomb drum  | Yes                          |
| Application   |                              |
| Suitable for the hotel and catering industry  | •                            |
| Suitable for retirement and care homes  | •                            |
| Suitable for facility management  | •                            |
| Suitable for launderettes   | •                            |
| Suitable for dry cleaners   | •                            |
| Suitable for commercial laundries   | •                            |
| Suitable for small businesses   | •                            |
| Suitable for universities, nurseries, and schools   | •                            |
| Suitable for hospitals  | •                            |
| Suitable for camp sites   | •                            |
| Suitable for sports clubs   | •                            |
| Suitable for beauty salons, spas and fit ness centers                                       | •                            |
| Suitable for doctors' and dentists' practices   | •                            |
| Suitable for the petrochemical industry   | •                            |
| Suitable for the food-processing industry   | •                            |
| Suitable for amusement parks and holiday complexes  | •                            |
| Suitable for public/community care facilities   | •                            |
| Performance data  |                              |
| Maximum evaporation capacity in l/hour and gal. qts./hour                                   | 2.60                         |
| Specific energy consumption in kWh/kg and kWh/p   | 0.20                         |
| Specific energy consumption for cottons/Normal drying, residual moisture 48% in kWh/kg      | 0.20                         |
| Specific energy consumption for mixed fabric/Normal drying, residual moisture 40% in kWh/kg | 0.17                         |
| Program cycle in min.   | 88                           |
| Program cycle time for cottons/Normal drying, residual moisture 48% in min.                 | 88                           |
| Program cycle time for cottons/Normal drying, residual moisture 40% in min.                 | 76                           |
| Controls  |                              |
| Control system  | M Touch Flex                 |
| Programmability   | programmable                 |
| Program controls  | Residual moisture controlled |
| Max. delay start in h   | 24                           |
| Countdown indicator   | •                            |
| Program sequence indicator  | •                            |
| Language can be selected easily at any time   | •                            |
| Standard electrical connection  |                              |
| Type of heating   | Heat pump                    |

## PDR 908 HP [EL]

Professional heat-pump dryer, Little Giants

With very low energy consumption and short program runtimes. Load capacity 18 (8.0) lb (kg).



EAN: 4002516195917 / Material number: 11204480 / Old Material Number: 52908159NAM

|   |                     |
|---|---------------------|
| Electrical connection                           | 2 AC 208-240V 60HZ  |
| Electric heater rating in kW                    | 0.00                |
| Total connected load in kW                      | 1.20                |
| Fuse rating in A                                | 30                  |
| NEMA plug: Twist Lock L6-30                     | •                   |
| <b>Dimensions and weight</b>                    |                     |
| External dimensions, net height in inches       | 33 1/2 (850)        |
| External dimensions, net width in inches        | 23 1/2 (596)        |
| External dimensions, net depth in inches        | 30 5/8 (777)        |
| External dimensions, gross height in inches     | 37 1/8 (940)        |
| External dimensions, gross width in inches      | 26 (660)            |
| External dimensions, gross depth in inches      | 32 3/8 (820)        |
| Net weight in lbs. (kg)                         | 157 (71.0)          |
| Gross weight in lbs. (kg)                       | 170 (77)            |
| <b>Emission levels</b>                          |                     |
| Emissions – sound pressure at workplace         | <70 dB(A) re 20 µPa |
| Heat output to the room in MJ/h and BTUs /h     | 3.60                |
| <b>Features</b>                                 |                     |
| Intelligent drum reversal                       | •                   |
| Axial airflow                                   | •                   |
| Fluff filter in the door                        | •                   |
| Low-maintenance heat exchanger filter system    | •                   |
| PerfectDry                                      | •                   |
| SoftLift drum ribs                              | •                   |
| Gentle tumble function                          | •                   |
| Condensed water drainage                        | •                   |
| Communication slot                              | •                   |
| Drying basket (optional)                        | •                   |
| Drum lighting                                   | •                   |
| Machine-independent accessories                 | •                   |
| <b>Efficiency and sustainability</b>            |                     |
| Contains fluorinated greenhouse gases           | •                   |
| Hermetically sealed system                      | •                   |
| Coolant   | R134a               |
| Refrigerant quantity in kg                      | 0.59                |
| Refrigerant global warming potential in kg CO2e | 1430                |
| Appliance global warming potential in kg CO2e   | 844.00              |
| <b>Connection options</b>                       |                     |
| Payment system (optional)                       | •                   |
| Optical interface for service access            | •                   |
| <b>Test certificate</b>                         |                     |
| WEEE  | •                   |
| c ETL US  | •                   |