


Quality construction and ease of installation make the BUEZ2 a popular choice in vertically-ducted economy hoods.

SIZE	WHITE ON WHITE	BLACK	STAINLESS STEEL	NON-DUCT CHARCOAL FILTER (replacement)
30-in.	BUEZ230WW	BUEZ230BL	BUEZ230SS	41F
36-in.	BUEZ236WW			41F

FEATURES	
Max. Blower CFM†	230
Control type	2-speed Rocker
Lighting	1-level intensity Designed for LED bulb (not included) A19, E26 base. If using incandescent bulb, 75 Watts max, purchase optional light guard #S99110437.
Grease Filter	1- Washable aluminum 8-3/4" x 10-1/2"
Installation Hardware	EZ1 brackets
ADA Compatible	yes
Duct Direction	Vertical (7 in. round - damper sold separately)
AC INPUT	
120 V, 60 Hz - 2.0 AMPS	
OPTIONAL ACCESSORIES	
7-in. Round Damper	BP87Q
ADA Wiring Kit	HAWSK3
Electrical Cord Kit	HCK44
MOUNTING HEIGHT	
18-in. to 24-in. from cooktop to bottom of hood	
LIMITED WARRANTY	
1-year See www.broan-nutone.com for full warranty text.	
FOR INDOOR USE ONLY	




† Max. blower CFM indicates the performance of the hood blower in open air and is not HVI certified.

Can be used to comply with LEED requirements.



HVI PERFORMANCE						
Duct Orientation	Size	Damper	Sones		CFM	
			Normal	High	Normal	High 0.1 in. w.g.
Vertical - Round	7-in.	BP87Q (purchase separately)	3.0	6.0	130	190



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.