

## GE® Stainless Steel Interior Dishwasher with Hidden Controls

## ELECTRICAL RATING

Voltage AC.....	120
Hertz.....	60
Total connected load amperage.....	8.9

Diagram illustrating the required clearances and dimensions for a kitchen island, specifically focusing on the underside of the countertop for utility entrances.

**Clearance Requirements:**

- Underside of countertop to floor: **32-3/8" min. to 34-3/4" max.**
- Clearance from side cabinets: **90°**

**Dimensions:**

- Island width: **24"**
- Countertop thickness: **3"**
- Shaded area (underside of countertop) width: **4"**
- Shaded area (underside of countertop) depth: **6"**
- Shaded area (underside of countertop) side clearance: **5"**

**Text:**

Electrical, drain and water supply line entrances must be confined to shaded areas to avoid interference with components



**ADA**  
COMPLIANT

Listed by  
Underwriters  
Laboratories

Specification Revised 7/16

# GDT226S

## *GE® Stainless Steel Interior Dishwasher with Hidden Controls*

### FEATURES AND BENEFITS

ADA Compliant with Low-Profile Installation – Great for 34" counter top heights and raised subfloors

3-Level Wash – Expect exceptionally clean table-ready dishes with powerful wash arms

Autosense Cycle – A beam of light measures soil levels and water temperature to adjust to the ideal cycle time

Piranha™ hard food disposer with removable filter – To ensure consistently clean items, this stainless steel blade rotates at 3,600 RPM to pulverize food particles and helps to prevent large particles from clogging the wash arms

Sanitize option (NSF Certified) – High-temperature rinse sanitizes and reduces by 99.999% the bacteria found on dishes

dBA 51

Model GDT226SSLSS – Stainless steel

Model GDT226SGLWW – White

Model GDT226SGLBB – Black

