



A range hood for every sense of style, control preference, and budget.



Step up to new levels of ventilation performance with the perfect look, optimal power, and a solution built for any budget. Enjoy deluxe control and lighting features, easy-to-clean filters, as well as unsurpassed blower performance in the new premium chimney hoods from Broan-NuTone.

Beautiful, Durable Finishes



STAINLESS



**BLACK
STAINLESS**



WHITE

Note: The last four digits of the model numbers are the width of the hood and the color. For example, model number EW4324SS is 24" in width and Stainless Steel in color.



STAINLESS

EW4824SS
EW4830SS
EW4836SS

BLACK STAINLESS

EW4830BLS, EW4836BLS
WHITE
EW4830WH



STAINLESS

EW4630SS, EW4636SS



STAINLESS

EW4324SS
EW4330SS
EW4336SS

BLACK STAINLESS

EW4330BLS, EW4336BLS

Entry level solutions packed with features

- Quiet 460 MAX Blower CFM operates at a best-in-class 1.5 sones at normal speed.
- Bright 2-level LED module (included).
- Tap-touch, three-speed capacitive control features a smooth, easy-to-clean surface.
- Dishwasher-safe deluxe filters feature quick-release latch for easy removal.
- CRT provides the ability to meet codes and reduce airflow to 300 CFM.
- 10 minute delay-off function keeps hood running after cooking to ensure smoke and odors have cleared the environment.
- Optional non-duct recirculation kit and filters available.
- Ducted/non-ducted telescopic flue extension accommodates 8' to 9' ceiling heights. Flue extensions available to accommodate ceiling heights from 9' to 10'.
- Installation brackets are included for easy installation.



STAINLESS

EWP1306SS, EWP1366SS



STAINLESS

EWT1306SS, EWT1366SS



Mid-range pricing with high-end features

- Quiet 640 MAX Blower CFM operates at a best-in-class <0.3 sones at normal speed.
- Brilliant 500 LUX 2-level LED modules (included).
- Tap-touch, four-speed capacitive control features a smooth, easy-to-clean surface.
- CRT provides the ability to meet codes and reduce airflow to 300 or 400 CFM.
- 15 minute delay-off function keeps hood running after cooking to ensure smoke and odors have cleared the environment.
- Dishwasher-safe hybrid baffle filters provide superior grease capture and professional styling.
- Optional non-duct recirculation kit and filters available.
- Ducted/non-ducted telescopic flue extension accommodates 8' to 9' ceiling heights. Flue extensions available to accommodate ceiling heights from 9' to 10'.
- Optional remote control (HCR4).
- Installation brackets are included for easy installation.

SPECIFICATIONS

Model	Width	MAX Blower CFM*	Blower	Sones	Volts	Amps	Duct	10' Flue Extension	Non-duct Kit	Non-duct Replacement Filter
EW43	24" 30" 36"	460	Internal	1.5	120	1.53	6" RD	AEW43SS AEW43BLS	ARKEW43	S99010473; 24", 30" S99010474; 36"
EW46	30" 36"	460	Internal	1.5	120	1.53	6" RD	AEW46SS	ARKEW46	S99010475
EW48	24" 30" 36"	460	Internal	1.5	120	1.53	6" RD	AEW48SS AEW48WH AEW48BLS	ARKEW48	S99010473; 24", 30" S99010474; 36"
EWP1	30" 36"	640	Internal	<0.3	120	3.7	6" RD	FXN58SS	ARKBWP	FILTERBWPTS
EWT1	30" 36"	640	Internal	<0.3	120	3.7	6" RD	FXN53SS	ARKBWT	FILTERBWPTS

* MAX Blower CFM indicates hood blower performance in open air. Find HVI rated performance for this model in the product specification sheet at Broan-NuTone.com