

GAS FREESTANDING RANGES AND VENTILATION PAIRING GUIDE



GAS FREESTANDING RANGES

30" REAR CONTROL

30" FRONT CONTROL

KFGG500E

KFGD500E

KFDD500ESS

KSGG700E

KSGB900E

YKSDB900ESS

KSDG950ESS

UNDER CABINET HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUB400GSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUB406GSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KVUB600DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KXU2830JSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KXU2836JSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |

WALL MOUNT AND ISLAND MOUNT HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVWB400DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVWB406DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KVWB600HBS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVWB606HBS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVIB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |

PRO STYLE VENTILATION AND LINERS

|                   |   |       |   |       |   |       |   |       |   |       |   |       |   |
|-------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUC600JSS  | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUC606JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVWC906JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - KVWC908JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVWC956JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - KVWC958JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - UVL5430JSS  | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - UVL6036JSS* | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - UVL6048JSS* | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |



\* Custom hood liners can be used with any of the following blower motors:

UXB1200DYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0600DYS (585 CFM)

\*\* Motor Class CFM rating

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

ELECTRIC FREESTANDING RANGES AND VENTILATION PAIRING GUIDE



ELECTRIC FREESTANDING RANGES

30" REAR CONTROL

30" FRONT CONTROL

YKFEG500E   YKFEG510ESS   YKFED500ESS   YKFID500ESS   YKSEG700E   YKSEB900E   KSEG950ESS   KSIB900ESS

UNDER CABINET HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUB400GSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUB406GSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KVUB600DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KXU2830JSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KXU2836JSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |

WALL MOUNT AND ISLAND MOUNT HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVWB400DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVWB406DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - KVWB600HBS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVWB606HBS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVIB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |

PRO STYLE VENTILATION AND LINERS

|                   |   |       |   |       |   |       |   |       |   |       |   |       |   |       |   |
|-------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUC600JSS  | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVUC606JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVWC906JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - KVWC908JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVWC956JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - KVWC958JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - UVL5430JSS  | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - UVL6036JSS* | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 48" - UVL6048JSS* | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |



\* Custom hood liners can be used with any of the following blower motors:

UXB1200DYS (1,170 CFM), UXH200DYS (1,200 CFM), UXB0600DYS (585 CFM)

\*\* Motor Class CFM rating

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

COMMERCIAL STYLE RANGES / RANGETOPS AND VENTILATION PAIRING GUIDE

| RANGES AND RANGETOPS              |                                            |       |          |       |            |       |                                            |       |          |       |            |       |                                            |       |          |       |            |  |
|-----------------------------------|--------------------------------------------|-------|----------|-------|------------|-------|--------------------------------------------|-------|----------|-------|------------|-------|--------------------------------------------|-------|----------|-------|------------|--|
|                                   | 30" COMMERCIAL STYLE<br>RANGES / RANGETOPS |       |          |       |            |       | 36" COMMERCIAL STYLE<br>RANGES / RANGETOPS |       |          |       |            |       | 48" COMMERCIAL STYLE<br>RANGES / RANGETOPS |       |          |       |            |  |
|                                   | KFDC500J                                   |       | KFGC500J |       | KCGC500JSS |       | KFDC506J                                   |       | KFGC506J |       | KCGC506JSS |       | KFDC558J                                   |       | KFGC558J |       | KCGC558JSS |  |
| UNDER CABINET HOODS               |                                            |       |          |       |            |       |                                            |       |          |       |            |       |                                            |       |          |       |            |  |
| 30" - KVUB400GSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVUB406GSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 30" - KVUB600DSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVUB606DSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 30" - KXU2830JSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KXU2836JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| WALL MOUNT AND ISLAND MOUNT HOODS |                                            |       |          |       |            |       |                                            |       |          |       |            |       |                                            |       |          |       |            |  |
| 30" - KVWB400DSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVWB406DSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 30" - KVWB600HBS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVWB606HBS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVIB606DSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| DOWNDRAFT                         |                                            |       |          |       |            |       |                                            |       |          |       |            |       |                                            |       |          |       |            |  |
| 30" - KXD4630YSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KXD4636YSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| PRO STYLE VENTILATION AND LINERS  |                                            |       |          |       |            |       |                                            |       |          |       |            |       |                                            |       |          |       |            |  |
| 30" - KVUC600JSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVUC606JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - KVWC906JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 48" - KVWC908JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          |  |
| 36" - KVWC956JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 48" - KVWC958JSS                  | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          |  |
| 30" - UVL5430JSS                  | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 36" - UVL6036JSS*                 | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          | ..... | ×                                          | ..... | ×        | ..... | ×          |  |
| 48" - UVL6048JSS*                 | ×                                          | ..... | ×        | ..... | ×          | ..... | ×                                          | ..... | ×        | ..... | ×          | ..... | ✓                                          | ..... | ✓        | ..... | ✓          |  |



\* Custom hood liners paired with commercial style ranges and rangetops must be used with blower: UXB1200DYS (1,170 CFM)

\*\* Motor Class CFM rating

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

GAS COOKTOP AND VENTILATION PAIRING GUIDE



GAS COOKTOPS

30" GAS COOKTOPS

36" GAS COOKTOPS

KCGS550ESS   KCGS950ESS   KCGD500GSS   KCGD500GSS   KCGS550ESS   KCGS950ESS   KCGD500GSS

UNDER CABINET HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUB400GSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KVUB406GSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 30" - KVUB600DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KVUB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 30" - KXU2830JSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KXU2836JSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |

WALL MOUNT AND ISLAND MOUNT HOODS

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVWB400DSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KVWB406DSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 30" - KVWB600HBS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KVWB606HBS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVIB606DSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |

DOWNDRAFT

|                  |   |       |   |       |   |       |   |       |   |       |   |       |   |
|------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KXD4630YSS | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KXD4636YSS | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |

PRO STYLE VENTILATION AND LINERS

|                   |   |       |   |       |   |       |   |       |   |       |   |       |   |
|-------------------|---|-------|---|-------|---|-------|---|-------|---|-------|---|-------|---|
| 30" - KVUC600JSS  | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - KVUC606JSS  | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 36" - KVWC906JSS  | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 48" - KVWC908JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 36" - KVWC956JSS  | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 48" - KVWC958JSS  | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |
| 30" - UVL5430JSS* | ✓ | ..... | ✓ | ..... | ✓ | ..... | ✓ | ..... | × | ..... | × | ..... | × |
| 36" - UVL6036JSS* | × | ..... | × | ..... | × | ..... | × | ..... | ✓ | ..... | ✓ | ..... | ✓ |
| 48" - UVL6048JSS* | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × | ..... | × |



\* Custom hood liners can be used with any of the following blower motors:  
UXB1200DYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0600DYS (585 CFM)

\*\* Motor Class CFM rating

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer’s responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

ELECTRIC COOKTOP AND VENTILATION PAIRING GUIDE



ELECTRIC COOKTOPS

30" ELECTRIC  
COOKTOPS

30" INDUCTION  
COOKTOPS

36" ELECTRIC  
COOKTOPS

36" INDUCTION  
COOKTOPS

KCES550H

KCED600G

KICU500X

KICU509X

KCES556H

KCED606G

KICU569X

UNDER CABINET HOODS

|                  |   |  |   |  |   |  |   |  |   |  |   |  |   |
|------------------|---|--|---|--|---|--|---|--|---|--|---|--|---|
| 30" - KVUB400GSS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KVUB406GSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 30" - KVUB600DSS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KVUB606DSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 30" - KXU2830JSS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KXU2836JSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |

WALL MOUNT AND  
ISLAND MOUNT HOODS

|                  |   |  |   |  |   |  |   |  |   |  |   |  |   |
|------------------|---|--|---|--|---|--|---|--|---|--|---|--|---|
| 30" - KVWB400DSS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KVWB406DSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 30" - KVWB600HBS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KVWB606HBS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 36" - KVIB606DSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |

DOWNDRAFT

|                  |   |  |   |  |   |  |   |  |   |  |   |  |   |
|------------------|---|--|---|--|---|--|---|--|---|--|---|--|---|
| 30" - KXD4630YSS | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KXD4636YSS | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |

PRO STYLE VENTILATION  
AND LINERS

|                   |   |  |   |  |   |  |   |  |   |  |   |  |   |
|-------------------|---|--|---|--|---|--|---|--|---|--|---|--|---|
| 30" - KVUC600JSS  | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - KVUC606JSS  | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 36" - KVWC906JSS  | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 48" - KVWC908JSS  | × |  | × |  | × |  | × |  | × |  | × |  | × |
| 36" - KVWC956JSS  | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 48" - KVWC958JSS  | × |  | × |  | × |  | × |  | × |  | × |  | × |
| 30" - UVL5430JSS  | ✓ |  | ✓ |  | ✓ |  | ✓ |  | × |  | × |  | × |
| 36" - UVL6036JSS* | × |  | × |  | × |  | × |  | ✓ |  | ✓ |  | ✓ |
| 48" - UVL6048JSS* | × |  | × |  | × |  | × |  | × |  | × |  | × |



**\* Custom hood liners can be used with any of the following blower motors:**  
UXB1200DYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0600DYS (585 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.