

FS30L7



24.63" x 18.5" x 17.75" (H x W x D)

Compact commercially listed manual defrost all-freezer with lock and reversible door

Highlights:

- Commercially listed to NSF-7 standards
- Compact size is ideal for countertop use
- Factory installed lock provides added security

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Compact dimensions	Sized for easy use on top of counters
Fully finished cabinet	Allows the unit to be used freestanding
Manual defrost	Static cooling system for improved temperature stability
Adjustable thermostat	Dial thermostat located inside the unit
Factory installed lock	Keyed lock for a secure interior
Reversible door	User-reversible door swing allows for more flexibility in placing the unit
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

FS30L7 Specifications:

Overview	
Nominal Height	25.0" (64 cm)
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Nominal Depth	18.0" (46 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	43.0 lbs. (20 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101053219
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)
Sound Level	33.3 dB

