# **PEP7036DT**

# GE Profile™ 36" Built-In Touch-Control Electric Cooktop


## **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**

**IMPORTANT:** Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

NOTE: 36" Ribbon cooktops are approved for use over select GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered.

Before installing, consult installation instructions packed with product for current dimensional data.


### APPROXIMATE COOKING DIMENSIONS



To insure accuracy, it is best to make a template when cutting the opening in the counter

### 13" MAX. depth of unprotected overhead cabinets 1 1/2" MIN. (30") and 2" MIN. (36") Clearance from cutout to nearest vertical wall or cabinet on right side of the unit below the 15" MIN. clearance height. 36" MIN. for 30" MIN. Clearance from counterton to unprotected overhead surface 15" MIN. height from countertop to nearest cabinet (including light rails) on both sides of 2" MIN. Clearance cookton from cutout to nearest vertical wall or cabinet on left side of the unit below the 15" MIN. clearance height.

#### **INSTALLATION ABOVE A WALL OVEN**



VOLTAGE (60HZ AC)	240V	208V
CONNECTED LOAD (MAX.)	9.7kW	7.3kW
CURRENT DRAW (MAX.)	40.4 Amps	35.1 Amps
RECOMMENDED CIRCUIT BREAKER	50 Amps	40 Amps

\*NOTE: Check local codes for required breaker size.









# **PEP7036DT**

# GE Profile™ 36" Built-In Touch-Control Electric Cooktop

### **FEATURES AND BENEFITS**

Power Boil on Tri- and Dual-Ring Elements

Precision Temperature Control

Glide Touch Controls - 11 Control Levels

Easy Clean Surface

Synchronized Elements

Chef Connect

Built-in WiFi

Compatible Cooktop with Smart Cookware


Keep Warm Setting

Control Lock

Hot Surface Indicator Lights

Fit Guarantee

Model PEP7036DTBB - Black on black



### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications.

Visit geappliances.com for more info.

#### COMPATIBLE COOKTOP WITH SMART COOKWARE

Smart pans easily pair with this smart cooktop to ensure you get the perfect cooking results. Accessories sold separately.

