

KM 7720 FR Induction Cooktop with 3 round cooking zones



- Intuitive quick selection via number sequences – Smart Select
- Versatile – 3 cooking zones, 1 extra large with diameter of 11 in
- With a width of 24 3/4 (626) in (mm) and stainless steel frame for proud-mounting
- Shortest heating-up times – TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611547 / Material number: 12074190 / Old Material Number: 26772000USA

Type of heating	
Fuel type	Induction
Construction type	
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless steel frame	•
Proud installation	•
Ring features	
No. of rings	3
Number of cooking areas	0
Maximum number of pans	3
1st cooking zone/cooking area	
Position	left center
Type	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3000
Max. rating in W	2600
Max. TwinBooster power rating in W	3700
2nd cooking zone/cooking area	
Position	rear right
Type	Variable cooking zone
Size in mm	Ø 140-190
Max. Booster power rating in W	2500
Max. rating in W	1850
Max. TwinBooster power rating in W	3000
3rd cooking zone/cooking area	
Position	front right
Type	Variable cooking zone
Size in mm	Ø 100-160
Max. Booster power rating in W	1700
Max. rating in W	1400
Max. TwinBooster power rating in W	2200
User convenience	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0	•
Operation via touchpad sensors	Smart Select
Keeping warm	•
Display color	Yellow
Permanent pan recognition	•
Pan/Pan-size sensors	•
Stop & Go function	•
Recall function	•
Minute minder	•
Automatic switch-off for all rings	•
AutoBoost	•
Individual setting options (e.g. acoustic signal tones)	•
Cleaning convenience	
Easy to clean ceramic glass	•

KM 7720 FR
Induction Cooktop
with 3 round cooking zones



EAN: 4002516611547 / Material number: 12074190 / Old Material Number: 26772000USA

Safety

Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•

Technical data

Dimensions in mm (width)	24 3/4 (626)
Dimensions in mm (height)	3 1/8 (78)
Dimensions in mm (depth)	21 1/2 (544)
Casing height incl. connection box in mm	2 7/8 (71)
Cutout dimensions in mm (width) with surface-mounted installation	22 3/8 (567)
Cutout dimensions in mm (depth) with surface-mounted installation	20 1/2 (518)
Weight in kg	30 (14)
Total rated load in kW	6.60-7.60
Voltage in V	0
Frequency in Hz	60

Standard accessories

Power cord	Yes
------------	-----