

## Dual Fuel Double Oven Slide-in Range

- Dual Fuel Range
- ProBake Convection®
- EasyClean® + Self Clean
- 18.5k BTU Power Burner
- Stainless Steel Touch Controls
- Scratch-resistant Finish
- Slide-in Design
- 7.3 cu. ft. Total Capacity
- LG ThinQ® Technology (Wi-Fi)



## LG SIGNATURE

### COLOR AVAILABILITY

 LUTD4919SN – Textured Steel™

### CAPACITY

Oven Capacity	7.3 cu. ft.
Upper Oven Capacity	3.0 cu. ft.
Lower Oven Capacity	4.3 cu. ft.

### OVEN FEATURES

Convection System	ProBake Convection® (Lower Oven Only)
Oven Cooking Modes	Upper: Bake, Speed Broil, Delay Bake, Delay Clean Lower: Bake, Broil, Convection Bake, Convection Roast, Multi-Rack Convection Baking, Delay Bake, Delay Clean, Proof, Warm
Air Sous Vide	No
Built-in Air Fry	No
Temperature Probe	Yes
Oven Racks	2 Heavy Duty, 1 Gliding
Number of Rack Positions	Upper: 2; Lower: 4
Broil Element (Watts)	Upper: Charcoal 3,000W (Infrared Grill); Lower: 3,800W / 6 Pass
Convection (Watts)	2,500W / 2 Turn (Lower Only)
Bake Element (Watts)	2,400W / 4 Pass (Exposed Bake) (Upper Only)
Convection Conversion	Yes (Lower Oven Only)
EasyClean®	Yes
Self Clean	Yes
GoCook Smart Oven Light	Yes (1 Light)
Door Lock	Yes
Automatic Safety Shut-Off	After 12 Hours

### COOKTOP FEATURES

Cooktop Type	Sealed
Number of Burners	5
Burner BTU (NG / LP)	
Left Front	12,000 / 10,000
Left Rear	9,100 / 9,100
Center	10,000 (Oval-Burner) / 10,000 (Warming Zone)
Right Front	18,500 / 12,500
Right Rear	5,000 / 5,000
Cooktop Burner Grate Material	Cast Iron
Continuous Grates	Yes

### CONTROLS

Cooktop Control Type	Front Control Knobs
Oven Control Type	Front Tilt, Stainless Steel Touch
Display	VFD (White / Red)
Language	English
Kitchen Timer	Yes
Timed Cook	Yes
Clock	12 Hr or 24 Hr (Option)
Temperature Unit of Measure	°F or °C
Cooking Complete Reminder Volume	High, Low, Off
Oven Control Lock	Yes

### CONVENIENCE

ADA Compliant	No
Sabbath Mode	No

### SMART FEATURES

Wi-Fi Enabled	Yes
ThinQ®	Yes
Proactive Customer Care	Yes
Voice Control	Amazon Alexa, Google Assistant
SmartDiagnosis™	Yes
3rd Party Recipe App	No

**FINISHES AND APPEARANCE**

Fingerprint & Smudge Resistant Exterior	No
Cooktop Finish	Textured Steel™
Handle / Knobs	Stainless Steel Appearance
Oven Door Feature	WideView™ Window

**TECHNICAL SPECS**

Fuel Type	Electric / NG / LP
Required Power Supply	120 / 208-240 V, 60 Hz, 3-Wire or 4-Wire
Minimum Circuit Rating	40 Amp
kW Rating at 208V	6.0 kW
kW Rating at 240V	6.9 kW
Power Cord Type	Not Included
Electrical Receptacle	4-Wire (14-50R); 3-Wire (10-50R)
Power Outlet Location	See Installation Diagram
Gas Supply Location	See Installation Diagram

**INCLUDED ACCESSORIES**

2 Heavy Duty Racks, 1 Gliding Rack, Griddle, Wok Grate, Rear Filler Kit, Temperature Probe, EasyClean® Kit (Spray Bottle & Scouring Pad), LP Conversion Kit

**OPTIONAL ACCESSORIES**

Slide-in Range Filler Kit (Side Gaps) LSFL301S

**DIMENSIONS / CLEARANCES / WEIGHTS**

Product Dimensions (W x H x D w/Handle)	29 7/8" x 36" x 28 15/16"
Product Height to Cooking Surface	36"
Cutout Dimensions (W x H x D)	30" x 36" x 25"
Carton Dimensions (W x H x D)	32 1/2" x 44" x 30 1/2"
Approx. Weight (Product / Carton)	196.2 lbs / 242.5 lbs

**LIMITED WARRANTY**

Parts and Labor	2 Years
-----------------	---------

**DIMENSIONS / CLEARANCES**

Provide proper clearance between the range and adjacent combustible surfaces. These dimensions must be met for safe use of your range. The location of the electrical outlet and pipe opening may be adjusted to meet specific requirements. The range may be placed with 0" clearance (flush) at the back wall.

