



Commercial Top-Load Washer

With 100 years of experience in the industry and features that streamline service, Whirlpool® Commercial Laundry machines provide performance with the quality you expect.

Featuring Factory-Installed Coin Drop and Coin Box

Commercial-Grade Features:

Choose a commercial-built product that withstands heavy traffic, regular use and performs continuously.



Commercial-Grade Construction

Built from thick-gauge, high-quality steel with an immensely powerful ½-HP motor to handle constant use and effectively deliver consistent, quality cleaning performance for any load—from the everyday to the extra-large.



Revenue Generating Options

Coin-drop machines let you set cycle prices to keep up with inflation, instead of being limited by the \$2 price maximum of coin-slide machines. You can also generate additional revenue with extra rinse and heavy soil cycle add-ons.



Deep Water Wash System

A traditional top-load wash experience with deep-water wash and rinse cycle options for vigorous cleaning action. The traditional flex-vane agitator provides four distinct wash profiles—from aggressive to gentle—designed to pull clothes from the top to the bottom of the wash basket.



Easy to Service

The metal console wraps completely around the back of the machine, making it easy to clean, and offering optimal protection against unexpected liquid spills or vapor. Front-panel accessibility provides fast entry to the motor, transmission and wash tub for streamlined self-service.

CAE2779JQ - 27" Commercial Washer

- 3.3 cu. ft. Capacity
- 700-RPM Spin Speed
- Display with Cycle Time
- Extra-Large Lid and Tub Opening
- 6' Inlet Hose and 6' Drain Hose Included

- Top-Lock and Coin Box Locks Factory-Installed, Keys Secured to Meter
- Factory Installed Coin Drop and Coin Vault Box
- 90-Day Labor / 2-Year Limited Parts Only Warranty*

*See whirlpoolcommerciallaundry.com for complete warranty details.


Commercial Top-Load Washer





Featuring Factory-Installed Coin Drop and Coin Box


Motor Size - HP (KW) V2 (.37)	Washer Specifications	
Modified Energy Factor (MEF sz)* 1.71 Integrated Water Factor (IWF)* 5.11 Approximate Water Usage — Gallons (Liters) Average Total Water Usage Per Cycle* 17.07 (64.6) Average Hot Water Usage, Warm Water Cycle 6.34 (23.99) Extract Speed — Max G-Force / Max RPM 144 / 700 Capacity Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Depth — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 27 (686) Dimensions	Model	CAE2779JQ
Integrated Water Factor (IWF)* 5.11 Approximate Water Usage — Gallons (Liters) Average Total Water Usage Per Cycle* 17.07 (64.6) Average Hot Water Usage, Warm Water Cycle 6.34 (23.99) Extract Speed — Max G-Force / Max RPM 144 / 700 Capacity Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Depth — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 23.8 (605) Dimensions Usage — in. (mm) 26 (660) Height — in. (mm) 27 (686) Depth — in. (mm) 29 (737) Lid Opening — in. (mm) 29 (737) Depth — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) 174 (78.9) Electrical Raquirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 10.18 Drain Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Motor Size — HP (KW)	1/2 (.37)
Approximate Water Usage — Gallons (Liters) Average Total Water Usage, Per Cycle* Average Hot Water Usage, Warm Water Cycle Average Hot Water Usage, Hot Water Cycle Extract Speed — Max G-Force / Max RPM Capacity Cylinder Volume — cu. ft. (liters) Cylinder Diameter — in. (mm) Depth — in. (mm) Lid Opening — in. (mm) Depth — in. (mm) Depth — in. (mm) Per Horizonia Width — in. (mm) Aut. (1,130) Lid Opening — in. (mm) Per Horizonia Width — in. (mm) Per Horizonia Per Horizoni	Modified Energy Factor (MEF _{J2})*	1.71
Average Total Water Usage Per Cycle* Average Hot Water Usage, Warm Water Cycle Average Hot Water Usage, Hot Water Cycle Extract Speed — Max G-Force / Max RPM Cylinder Volume — cu. ft. (liters) Cylinder Diameter — in. (mm) Cylinder Depth — in. (mm) Depth — in. (mm) Lid Opening — in. (mm) Depth — in. (mm) Depth — in. (mm) Depth — in. (mm) Peth — in. (mm) Depth — in. (mm) Average Hot Water Usage, Warm Water Cycle 6.34 (23.99) Extract Speed — Max G-Force / Max RPM 144 / 700 Capacity Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 21 (686) Dimensions Width — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight Uncrated — Ibs. (kg) 156 (70.8) Crated — Ibs. (kg) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Integrated Water Factor (IWF)*	5.11
Average Hot Water Usage, Warm Water Cycle Average Hot Water Usage, Hot Water Cycle 6.34 (23.99) Extract Speed — Max G-Force / Max RPM 144 / 700 Capacity Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 21 (686) Dimensions Width — in. (mm) 22 (660) Height — in. (mm) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 29 (737) Depth — in. (mm) Approximate Weight Uncrated — Ibs. (kg) Crated — Ibs. (kg) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps Water Inlet / Hose Operating Pressure PSI (bar) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Approximate Water Usage — Gallons (Liters)	
Average Hot Water Usage, Hot Water Cycle Extract Speed — Max G-Force / Max RPM 144 / 700 Capacity Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 23.8 (605) Dimensions Width — in. (mm) 26 (660) Height — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 29 (737) Depth — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) Crated — lbs. (kg) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Average Total Water Usage Per Cycle*	17.07 (64.6)
Extract Speed — Max G-Force / Max RPM Capacity Cylinder Volume — cu. ft. (liters) Cylinder Diameter — in. (mm) Cylinder Depth — in. (mm) Cylinder Depth — in. (mm) Depth — in. (mm) Depth — in. (mm) Lid Opening — in. (mm) Depth — in. (mm) Crated Dimensions Width — in. (mm) Depth — in. (mm) Peth — in. (mm) Crated Dimensions Width — in. (mm) Depth — in. (mm) Peth — in. (mm) Depth — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) Depth — in. (mm) 17 (478) Depth — in. (mm) Approximate Weight Uncrated — lbs. (kg) Crated — lbs. (kg) Tyl (78.9) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) Drain Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m)	Average Hot Water Usage, Warm Water Cycle	0.56 (2.1)
Capacity 3.3 (92.6) Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 23.8 (605) Dimensions Width — in. (mm) Width — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Vidth — in. (mm) Width — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight 156 (70.8) Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 156 (70.8) Electrical Requirements 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Average Hot Water Usage, Hot Water Cycle	6.34 (23.99)
Cylinder Volume — cu. ft. (liters) 3.3 (92.6) Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 23.8 (605) Dimensions Width — in. (mm) 27 (686) Depth — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Vidth — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight 156 (70.8) Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Extract Speed — Max G-Force / Max RPM	144 / 700
Cylinder Diameter — in. (mm) 20.8 (528) Cylinder Depth — in. (mm) 23.8 (605) Dimensions Width — in. (mm) 27 (686) Depth — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Capacity	
Cylinder Depth — in. (mm) 23.8 (605) Dimensions 27 (686) Width — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) Width — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight 49 (1,255) Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements 15 Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 0 Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Cylinder Volume — cu. ft. (liters)	3.3 (92.6)
Dimensions Width — in. (mm) 27 (686) Depth — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 0 Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Cylinder Diameter — in. (mm)	20.8 (528)
Width — in. (mm) 27 (686) Depth — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) Width — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements 15 Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 – 100 (1 – 8) Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8)	Cylinder Depth — in. (mm)	23.8 (605)
Depth — in. (mm) 26 (660) Height — in. (mm) 44.5 (1,130) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) Width — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight 49 (1,255) Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 – 100 (1 – 8) Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Dimensions	
Height — in. (mm) Lid Opening — in. (mm) 17 (432) Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) Inlet Hose Length — ft. (m) Drain Hose Length — ft. (m) 6 (1.8)	Width — in. (mm)	27 (686)
Lid Opening — in. (mm) 17 (432) Crated Dimensions 29 (737) Width — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight 156 (70.8) Uncrated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 - 100 (1 - 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Depth — in. (mm)	26 (660)
Crated Dimensions Width — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Height — in. (mm)	44.5 (1,130)
Width — in. (mm) 29 (737) Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight 156 (70.8) Uncrated — lbs. (kg) 174 (78.9) Electrical Requirements 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 - 100 (1 - 8) Operating Pressure PSI (bar) 20 - 100 (1 - 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Lid Opening — in. (mm)	17 (432)
Depth — in. (mm) 27.5 (699) Height — in. (mm) 49 (1,255) Approximate Weight Uncrated — lbs. (kg) Uncrated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Crated Dimensions	
Height — in. (mm) Approximate Weight Uncrated — lbs. (kg) Crated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Rating — voltage / Hz Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) Inlet Hose Length — ft. (m) Orain Hose Length — ft. (m) 6 (1.8)	Width — in. (mm)	29 (737)
Approximate Weight Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Depth — in. (mm)	27.5 (699)
Uncrated — lbs. (kg) 156 (70.8) Crated — lbs. (kg) 174 (78.9) Electrical Requirements Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Height — in. (mm)	49 (1,255)
Crated — Ibs. (kg) 174 (78.9) Electrical Requirements 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 - 100 (1 - 8) Operating Pressure PSI (bar) 20 - 100 (1 - 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Approximate Weight	
Electrical Requirements 120 / 60 Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 - 100 (1 - 8) Operating Pressure PSI (bar) 20 - 100 (1 - 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Uncrated — lbs. (kg)	156 (70.8)
Electrical Rating — voltage / Hz 120 / 60 Breaker / Fuse — amps 15 Water Inlet / Hose 20 - 100 (1 - 8) Operating Pressure PSI (bar) 20 - 100 (1 - 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Crated — lbs. (kg)	174 (78.9)
Breaker / Fuse — amps 15 Water Inlet / Hose 20 – 100 (1 – 8) Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Electrical Requirements	
Water Inlet / Hose 20 – 100 (1 – 8) Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Electrical Rating — voltage / Hz	120 / 60
Operating Pressure PSI (bar) 20 – 100 (1 – 8) Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Breaker / Fuse — amps	15
Inlet Hose Length — ft. (m) 6 (1.8) Drain Hose Length — ft. (m) 6 (1.8)	Water Inlet / Hose	
Drain Hose Length — ft. (m) 6 (1.8)	Operating Pressure PSI (bar)	20 - 100 (1 - 8)
	Inlet Hose Length — ft. (m)	6 (1.8)
Warranty 2-Year Limited / 90-Day Labo	Drain Hose Length — ft. (m)	6 (1.8)
	Warranty	2-Year Limited / 90-Day Labor

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Whirlpool reserves the right to change specifications without notice.















2-YEAR LIMITED PARTS ONLY WARRANTY / 90-DAY LABOR

For 90 days from the date of original purchase, when this commercial appliance is installed, maintained, and operated according to instructions attached to or furnished with the product, Whirlpool Corporation (hereafter "Whirlpool") will pay for factory-specified replacement parts and repair labor to correct defects in materials or workmanship that existed when this commercial appliance was purchased. For the first two years from the date of purchase, when this major appliance is installed, maintained, and operated according to the instructions attached to or furnished with the product, Whirlpool will pay for factory-specified replacement parts to correct defects in materials or workmanship that existed when this commercial appliance was purchased.