PRG304WH

30-INCH GAS PRO HARMONY® RANGE












FEATURES & BENEFITS

- ★ Exclusive, Star® Burner-most even heating, unsurpassed flame coverage
- ★ ExtraLow®, the widest simmer temperature control as low as 100°F
- ★ 2 ExtraLow® burners for simmering, melting, or holding long durations
- ★ QuickClean Base® designed for easy surface cleaning
 - Convection Bake offers precise multi-level baking results

TECHNICAL DETAILS	
Circuit Breaker	15 A
Volts	120 V, 60Hz
Energy Source	Gas
Plug Type USA	120V - 3 Prong
Power Cord Length	65" (1,651mm)
Gas Supply	3/4"
WARRANTY	
Limited Warranty, Entire Appliance,	2 Year

SEE PAGE 2 FOR INCLUDED AND OPTIONAL ACCESSORIES

RANGETOP



Total number of cooktop Burners	4
1 – Power of Back Left Burner BTU	15,000 and XLO
2 – Power of Front Left Burner BTU	18,000 and XLO
3 – Power of Back Right Burner BTU	15,000
4 – Power of Front Right Burner BTU	18,000

OVEN	
Oven Capacity	4.6 cu. ft.

Cooking Modes

Bake, Convection Bake, Roast, Broil, Extended Bake

Sabbath	Yes (as Extended Bake – Knob Control)
Self Clean	No
Telescopic Rack(s)	1
Interior Lights	2
Bake Power	20,500 BTU
Broil Power	17,500 BTU
Home Connect™ (Wi-Fi Enabled)	No
Cavity Interior Dimensions (HxWxD)	16 1/2 " x 26" x 18 5/8 "
Cavity Usable Dimensions (HxWxD)	11 1/4" x 22 3/8" x 16 3/4"

DIMENSIONS & WEIGHT	
Overall Appliance Dimensions (HxWxD)	35 3/4"-36 3/4" × 29 15/16" × 24 5/8"
Required Cutout Size (HxWxD)	35 3/4 "-36 3/4 " × 30" × 24"
Net Weight	306 lbs.

★ THERMADOR® EXCLUSIVE

Page 1 of 6 11 / 18



PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE

ACCESSORIES (INCLUDED)

1 Telescopic Rack, 2 Standard Racks, 1 Lg. Broil Pan, Island Trim

ACCESSORIES (OPTIONAL)



PWOKRINGHC

Wok Ring



PAGRIDDLE

Professional Griddle, Sits on Top of Grates Over 2 Star Burners, High-Release Coating



PAKNOBLUWH

Metallic Blue Knob Kit



PAALTKITGW

Natural Gas Models from 5,400 ft.-10,200 ft.



PA12CHPBLK

Chopping Block / Cutting Board



PA30WLBH

Pro Harmony 7" Low Back Backguard*



PALPKITGW

LP Conversion Kit Gas Pro Ranges (4 & 6 Burner)



Contact Customer Support


Propane Gas or Dual-Fuel Models Connected to LP Gas from 10,000 ft.–10,200 ft.

Page 2 of 6 11 / 18


^{*}Models PCG305xx, PRD305xx, and PRD606xx are suitable for 0" rear clearance to combustible surfaces. All other models: when using the included Island Trim a minimum 6" (152 mm) rear clearance is required to a combustible surface. When installing against a combustible surface, a Thermador Down Backguard is required for a 0" rear clearance to the combustible surface. A Thermador Low Backguard must be purchased separately. A rear clearance to a surface covered in a noncombustible material (metal, ceramic tile, brick, marble, or stone) is 0" when using the included Island Trim. Clearances of less than 6" (152 mm) should be approved by the local codes and/or by the local authority having jurisdiction. Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA.



30-INCH RANGE DIMENSIONS



30-INCH RANGE CUTOUT DIMENSIONS




Page 3 of 6 11 / 18





30-INCH RANGE CUTOUT DIMENSIONS




Page 4 of 6 11 / 18



PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE

30-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "LOW BACK"

NOTE: A 36-inch minimum clearance is required between the top of the cooking surface and the bottom of an unprotected cabinet. A 30-inch clearance can be used when the bottom of the wood or metal cabinet is protected by not less than 1/4 inch of a flame retardant material covered with not less than No. 28 MSG sheet steel, 0.015 inch (0.4 mm) thick stainless steel, 0.024 inch (0.6 mm) aluminum, or 0.020 inch (0.5 mm) thick copper.




⚠ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition).
Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA. Clearances of less than 12" (305 mm) must be approved by the local codes and/or by the local authority having jurisdiction.

Page 5 of 6 11 / 18



PROFESSIONAL SERIES, STANDARD-DEPTH, PORCELAIN COOKTOP SURFACE

30-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "FLUSH ISLAND TRIM"



 Δ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition). Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA. Clearances of less than 12" (305 mm) must be approved by the local codes and/or by the local authority having jurisdiction.

These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

1 800 735 4328 | USA THERMADOR.COM | CANADA THERMADOR.CA | @2018 BSH HOME APPLIANCES CORPORATION. ALL RIGHTS RESERVED.

Page 6 of 6 11 / 18