

# **Product Specifications**

# **Front-Venting Freezers**

- Create a seamless, built-in look that adds a clean, professional appearance, ideal for open kitchens or customer-facing areas.
- Ensure efficient operation in high-traffic areas by directing heat away from the interior, maintaining consistent airflow even in compact spaces.
- Unidirectional casters included for easy maneuverability and stability in tight spaces.







UCFZ332-SS11A


Model	Description	Voltage/Hz/Phase/Amps	Shipping Weight
UCFZ327-SS11A	27" Front-Venting 1 Door Freezer	115 / 60 / 1 / 6	231 lb
UCFZ332-SS11A	32" Front-Venting 1 Door Freezer	115 / 60 / 1 / 6	253 lb

Specifications	
UCFZ327-SS11A dimensions: 33 <sup>31</sup> / <sub>32</sub> " H x 27 <sup>21</sup> / <sub>32</sub> " W x 31 <sup>3</sup> / <sub>4</sub> " D	
UCFZ332-SS11A dimensions: 33 31/32" H X 32 9/32" W X 31 13/16" D	
UCFZ327-SS11A: volume of 6.39 cu ft, 1 epoxy coated shelf	
UCFZ332-SS11A: volume of 8 cu ft, 1 epoxy coated shelf	
AISI 304 stainless steel interior and exterior	
Autodefrost	
CFC-free high density polyurethane insulated cabinet	
Electronic Control	
Environmentally friendly R290 refrigerant	
Epoxy coated, sealed evaporator eliminates potential corrosion	
Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P	
NSF/ANSI Standard 7 compliant	
Temperature range: -13°F to 14°F	




# **Product Specifications • Front-Venting Freezers**


#### Front (UCFZ327-SS11A)




### Front (UCFZ332-SS11A)




#### Top



Top



## Side (all models)









#### **Commercial Warranty**

3 Year (parts & labor) / 5 year sealed system (parts) See complete warranty for details

