

PERFORMANCE DATA SHEET
Model: PurePour™ PWF-1™ Using Replacement Cartridge FPPWFO1™

APPLICATION GUIDELINES / CONDITIONS OF USE
Water Supply: Potable Water
Water Temp.: Max. 100°F (38°C), Min. 33°F (0.6°C)
Water Pressure: 30 - 100 psi (206.8 - 689.5 kPa)
Service Flow: 0.65 gpm maximum (2.46 lpm)
It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised.

WARNING
Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.
Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system.
Your Water Filtration system will withstand up to 100 lbs/in² (psi) water pressure.
To reduce the risk associated with choking: DO NOT allow children under 3 years of age to have access to small parts during the installation of this product.
To reduce the risk associated with the ingestion of contaminants: DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after use of the system.

REPLACEMENT CARTRIDGE INFORMATION
Replacement Element: FPPWFO1™. For estimated cost of replacement elements please call 1-800-374-4432 or visit us on the web at Frigidaire.com.
PERFORMANCE DATA
MODEL: PurePour™ PWF-1™. Use the replacement cartridge FPPWFO1™.
Certified by IAPMO R&T against NSF/ANSI Standard 42, Standard 53, Standard 401, and CSA B483.1 for the reduction of substances listed below and NSF/ANSI/CAN 372.
SYSTEM SPECIFICATIONS
Capacity: 125 gallons (473 liters)

CAUTION
To reduce the risk associated with property damage due to water leakage or flooding:
Read and follow the Use and Care Manual before installation and use of this system.
Change the disposable filter cartridge at the recommended interval; You MUST replace the disposable filter cartridge every 6 months or sooner.
Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.
Installation and use MUST comply with all state and local plumbing codes.
Protect from freezing, remove filter cartridge when temperatures are expected to drop below 33°F (4.4°C).
DO NOT install systems in areas where ambient temperatures may go above 110°F (43.3°C).
DO NOT install on hot water supply lines. The maximum operating water temperature of this filter system is 100°F (37.8°C).

Please refer to the use and care manual for proper maintenance and operation. If this device is not maintained and operated as specified in the use and care manual, there is a risk of exposure to contaminants. For more information, visit Frigidaire.com or the State Water Resources Control Board's Internet Web site at swrcb.ca.gov. Patents: This product may be covered by one or more US patents identified at Electroluxipnotice.com

Table with 4 columns: Substance Reduction, NSF/ANSI Specified Challenge Concentration, Maximum Permissible Concentration, NSF Reduction Requirements. Rows include Chlorine, Nominal Particulate Class I, Microplastics, Asbestos, Atrazine, Benzene, Carbofuran, Cysts*, Endrin, Lead pH 6.5, Lead pH 8.5, Lindane, Mercury pH 6.5, Mercury pH 8.5, O-Dichlorobenzene, P-Dichlorobenzene, Perfluorooctanoic acid (PFOA), Perfluorooctane sulfonate (PFOS), Tetrachloroethylene, VOC**, Toxaphene (Pesticide), 2,4-D (Herbicide), Atenolol, Bisphenol A, Estrone, Ibuprofen (Pharma), Naproxen, Nonylphenol, Phenytoin, Trimethoprim.

* Based on the use of Microsphere Cysts
**VOC reduction claim in table above indicates the PurePour PWF-1 model reduces the concentration of all of the following contaminants (over):

VOC Reduction Table

Substance Reduction	NSF/ANSI Specified Challenge Concentration	Maximum Permissible Concentration	NSF Reduction Requirements
Alachlor	50 ug/L	1ug/L	> 98
Atrazine	100 ug/L	3 ug/L	> 97
Benzene	81 ug/L	1ug/L	> 99
Carbofuran	190 ug/L		
Carbon Tetrachloride	78 ug/L	1.8 ug/L	98
Chlorobenzene	77 ug/L	1ug/L	> 99
Chloropicrin	15ug/L	0.2 ug/L	99
2, 4 -D	110 ug/L	1.7 ug/L	98
Dibromochloropropane (DBCP)	52ug/L	0.02 ug/L	> 99
O-Dichlorobenzene	80ug/L	1ug/L	
P-Dichlorobenzene	40 ug/L		> 98
1, 2-Dichloroethane	88 ug/L	4.8ug/L	95
1, 1-Dichloroethylene	86 ug/L	1ug/L	> 99
Cis-1, 2-Dichloroethylene	170 ug/L	0.5 ug/L	
Trans-1, 2-Dichloroethylene	83 ug/L	1ug/L	
1, 2-Dichloropropane	80 ug/L		
Cis-1, 3-Dichloropropylene	79 ug/L		
Dinoseb	170 ug/L	0.2 ug/L	99
Endrin	53 ug/L	0.59 ug/L	
Ethylbenzene	880 ug/L	1ug/L	> 99
Ethylene Dibromide (EDB)	44 ug/L	0.02 ug/L	
Haloacetonitriles (HAN)			
Bromochloroacetonitrile	22 ug/L	0.5 ug/L	98
Dibromoacetonitrile	24 ug/L	0.6 ug/L	
Dichloroacetonitrile	9.6 ug/L	0.2 ug/L	
Trichloroacetonitrile	15 ug/L	0.3 ug/L	
Haloketones (HK)			
1, 1-Dichloro - 2-Propanone	7.2ug/L	0.1ug/L	99
1, 1, 1-Trichloro - 2-Propanone	8.2 ug/L	0.3 ug/L	96
Heptachlor	25 ug/L	0.01ug/L	> 99
Heptachlor Epoxide	10.7 ug/L	0.2 ug/L	98
Hexachlorobutadiene	44 ug/L	1ug/L	> 98
Hexachlorocyclopentadiene	60 ug/L	0.002 ug/L	> 99
Lindane	55 ug/L	0.01ug/L	
Methoxychlor	50 ug/L	0.1ug/L	
Pentachlorophenol	96 ug/L	1ug/L	
Simazine	120 ug/L	4 ug/L	> 97
Styrene	150 ug/L	0.5 ug/L	> 99
1, 1, 2, 2-Tetrachloroethane	81ug/L	1ug/L	
Tetrachloroethylene			
Toluene	78 ug/L		
2, 4, 5-TP (Silvex)	270 ug/L	1.6 ug/L	99
Tribromoacetic Acid	42 ug/L	1ug/L	> 98
1, 2, 4-Trichlorobenzene	160 ug/L	0.5 ug/L	> 99
1, 1, 1-Trichloroethane	84 ug/L	4.6 ug/L	95
1, 1, 2-Trichloroethane	150 ug/L	0.5 ug/L	> 99
Trihalomethanes (includes)	300 ug/L	1.5 ug/L	95
Chloroform (surrogate chemical)			
Bromoform			
Bromodichloromethane			
Chlorodibromomethane			
Xylenes (total)	70 ug/L	0.1 ug/L	> 99



This filter is certified by the Water Quality Association to
WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à
la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según
WQA/ASPE/ANSI-803 por sostenibilidad.