

FS30L



24.63" x 18.5" x 17.75" (H x W x D)

Compact manual defrost all-freezer for medical/general purpose use, with lock and reversible door

Highlights:

- Compact size is ideal for countertop use
- Factory installed lock provides added security
- Designed for general purpose use in medical and scientific facilities

Product Features:

Compact dimensions	Sized for easy use on top of counters
Fully finished cabinet	Allows the unit to be used freestanding
Manual defrost	Static cooling system for improved temperature stability
Adjustable thermostat	Dial thermostat located inside the unit
Factory installed lock	Keyed lock for a secure interior
Reversible door	User-reversible door swing allows for more flexibility in placing the unit
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices

FS30L Specifications:

Overview	
Nominal Height	25.0" (64 cm)
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Nominal Depth	18.0" (46 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	43.0 lbs. (20 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101029207
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)
Sound Level	33.3 dB

