

# Performance Data Sheet for InSinkErator Filter System Model: F-201 Replacement Cartridge: F-201R

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42.



Tested & Certified for NSF International against NSF/ANSI Standard 42 in the following InSinkErator Systems Only: GN100, HC100, GN2200, HC2200, GN 2215, HC2215, H3300 or HC 3300 for the reduction of claims specified on the Performance Data Sheet.

Note that while the testing was performed under standard laboratory conditions, actual performance may vary.

Capacity 500 Gallons (1,392 Liters) Contaminant Reduction Determined by NSF testing.

Substance Reduction	Average Influent	NSF specified Challenge Concentration	Avg % Reduction	Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L $\pm$ 10%	$\geq$ 97.5%	0.05 mg/L	N/A	$\geq$ 50%	Chlorine: J-00341226
Nominal Particulate Class III, $\geq$ 5 $\mu$ m to < 15 $\mu$ m	61,000 pts/mL	At least 10,000 particles/mL	99.9%	25 pts/mL	N/A	$\geq$ 85 %	Particulate: J-00341227

## ⚠ WARNING

**Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.**

- Check with your local public works department for plumbing codes. You must follow their guidelines as you install the water filtration system.
- Your water filtration system will withstand up to 80 pounds per square inch (psi) water pressure. If your water pressure exceeds 80 psi (550 kPa), you must install a pressure limiting valve.

**To reduce the risk associated with the ingestion of contaminants:**

- DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- DO NOT use with water that is unsafe or of unknown quality with respect to any contaminants.
- DO NOT use on a water source that does not meet the water quality and safety standard criteria set forth by your local regulatory body. ONLY install on a potable cold-water supply (your water must be safe for consumption prior to installing and using this water filter).

Application Guidelines/Water Supply Parameters
Service Flow ..... 0.75 gpm (2.8 lpm)
Water Supply ..... Potable Water
Water Pressure..... 20-80 psi (138-550 kPa)
Water Temperature..... 33°F - 100°F (0.6°C - 38°C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

Replacement Cartridge: F-201R. For estimated costs of replacement elements, please call 1-800-558-5700 (US) or (0) 1 923 297 880 (UK) or visit [www.insinkerator.com](http://www.insinkerator.com), [shop.insinkerator.com](http://shop.insinkerator.com) or [www.insinkerator.co.uk/filters](http://www.insinkerator.co.uk/filters) to opt in for an auto replenishment program.

## NOTICE

**To reduce the risk associated with property damage due to water leakage or flooding:**

- Read and follow Use Instructions before installation and use of this system.

**To reduce the risk of water leakage or flooding and to ensure optimal filter performance:**

- Change the disposable filter cartridge every six months or sooner if you observe a noticeable reduction in water flow rate.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.
- For systems using two handle model faucets, operate only one handle at a time.
- For questions or concerns, please contact Customer Service at 1-800-558-5700 (US) or (0) 1 923 297 880 (UK).