

KMR 1134-3 G EDST/CLST

RangeTop

with ?? burners for professional applications



- Professional design – 36 (914) in (mm) wide in stainless steel with Clean Touch Steel™ finishing
- Direct control – metal knobs with light ring
- Easy cleaning – ComfortClean dishwasher-safe grates
- Broad performance spectrum – burner w. up to 19,500 BTU (5.7 kW)
- Convenient and safe – automatic re-ignition for all burners

EAN: 4002516534969 / Material number: 11852340 / Old Material Number: 26113470USA

Heating type	
Fuel type	Gas
Design	
Rangetop	•
Design	
Casing	Stainless steel
Front panel	CleanSteel
Genuine metal knobs	•
Cast iron pot rests (matte black enameled)	•
Cooking zone details	
Number of gas burners	6
1st cooking zone/cooking area	
Position	front left
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
2nd cooking zone/cooking area	
Position	rear left
Type	High-speed burner
Minimum power output in BTU/hr	1200
Maximum power output in BTU/hr	12500
Max. rating in W	3700
3rd cooking zone/cooking area	
Position	rear right
Type	High-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	13600
Max. rating in W	4000
4th cooking zone/cooking area	
Position	rear right
Type	High-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	13600
Max. rating in W	4000
5th cooking zone/cooking area	
Position	front right
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
6th cooking zone/cooking area	
Position	front center
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
8th cooking zone/cooking area	
True Simmer function	•

KMR 1134-3 G EDST/CLST

RangeTop

with ?? burners for professional applications



EAN: 4002516534969 / Material number: 11852340 / Old Material Number: 26113470USA

User convenience

Operation via genuine metal knobs with backlit

•

Cleaning convenience

Dishwasher-safe trivets

•

Single-piece cooktop surround

•

Safety

Automatic re-ignition

•

Technical data

Dimensions (width) in in. (mm) 36 (914)

Dimensions (height) in in. (mm) 7 5/8 (191)

Dimensions (depth) in in. (mm) with bullnose 27 1/4 (692)

Dimensions (depth) in in. (mm) without bullnose 25 5/8 (650)

Weight in lbs. (kg) 121 (55)

Total output in BTU/hr 98200

Total connected load in kW 32.20

Voltage in V 120

Fuse rating in A 10


Number of phases 1

Power cord length in in. (m) 3 (1.2)

KMR 1134-3 G EDST/CLST

RangeTop

with ?? burners for professional applications



KMR1134, KMR1135, KMR1136, KMR1134-3, KMR1135-3, KMR1136-3 (Installation drawing)

1) Side view, 2) Front view, 3) Rear view, 4) Gas Connection, 5) Electrical connection