25.5 cu. ft. Counter-Depth MAX™ French Door Refrigerator

- Counter-Depth MAX[™]
- 25.5 cu. ft. Capacity
- InstaView® Door-in-Door®
- Edge-to-Edge InstaView® Design
- Dual Ice Maker
- Slim SpacePlus® Ice System
- Cool Guard Stainless Steel Back Wall
- LED Lighting
- LG ThinQ® Technology (Wi-Fi)
- ThinQ Care & ThinQ Up











COLC)R	٩V	A II A	ABII	IT)	7
COLC	,,,		<u> </u>	15115		4

		LF26C6360S -	$PrintProof^{\texttt{®}}$	Stainless	Steel
--	--	--------------	---------------------------	-----------	-------

Refrigerator (cu. ft.)	16.9
Freezer (cu. ft.)	8.6
Total Capacity (cu. ft.)	25.5
ENERGY	
Energy Consumption (kWh / Year)	699
ENERGY STAR® Certified	Yes
WATER & ICE SYSTEM	
In-Door Dispenser	Yes, Ice & Water
In-Door Ice System	Slim SpacePlus®
In-door Ice Maker - Ice Type	Cubed & Crushed
In-door Ice Maker - Daily Ice Production	3.0 lbs. (3.3 lbs. w/IcePlus®)
In-door Ice Maker - Ice Storage Capacity	3.0 lbs.
Freezer Ice Maker	Yes (1)
Freezer Ice Maker - Ice Type	Cubed
Freezer Ice Maker - Daily Ice Production	2.5 lbs. (2.7 lbs. w/IcePlus®)
Freezer Ice Maker - Ice Storage Capacity	4.0 lbs.
Dispenser Light	Yes
Water Filter	LT1000P (NSF-Certified*)
COOLING	


Water Filter	LT1000P (NSF-Certified*)	
COOLING		
Compressor Type	Smart Inverter Compressor	
Dual Evaporators	No (1 evaporator)	
Multi-Air Flow System	Yes	
Door Cooling+	Yes	
Temperature Sensors	2	
Fresh Air Filter	Yes	


CONVENIENCE				
Display Type	Smooth Touch Control / White LED			
Temperature Controls	Electronic / Digital			
Door Alarm	Yes			
Child Lock	Yes			
Auto Closing Door Hinge	Yes (Only left door)			
ADA Compliant	Yes			
Sabbath Mode	Yes			
LoDecibel® Quiet Operation	Yes			
REFRIGERATOR				
No. of Shelves	4 split (4 Fixed)			
Cantilevered Shelves	Yes			
Shelf Construction	Spill Protector™ Tempered Glass			
Crisper Bins	2			
Glide N' Serve® Pantry Drawer	Yes			
Cool Guard	Yes			
Refrigerator Light	Yes			
REFRIGERATOR DOOR	FRIGERATOR DOOR			
Edge-to-Edge InstaView®	Yes			
InstaView® Door-in-Door®	Yes			
Door-in-Door® with ColdSaver® Panel	No			
No. of Door Bins	8 Total			
Door Bin Construction	1 Piece (Clear)			
FREEZER				
Freezer Type	Pull Drawer			
Freezer Drawers	2-Tier Organization			
DuraBase® Solid Drawer Base	Yes			
Drawer Divider	Yes			
Ice Storage	Ice Bin in Freezer			
Freezer Light	LED Lighting			
Freezer Handle	Pocket Handle			

SMART FEATURES	
Wi-Fi Enabled	Yes
ThinQ® Technology	Yes
ThinQ Care	Yes
ThinQ Up	Yes
Voice Control	Google Assistant, Amazon Alexa
SmartDiagnosis™	Yes
Remote Monitoring	Yes
MATERIALS AND FINISHES	163
Hidden Hinges	Yes
Surface	Smooth
Fingerprint & Smudge Resistant	Yes
Exterior	
Handles	Pocket Handles
ACCESSORIES	
Replacement Water Filter	LT1000P
Replacement Fresh Air Filter	LT120F
TECHNICAL SPECS	
Required Power Supply	115 V, 60 Hz, 15 Amp
Plug Type	3-Prong
Power Cord Location	Тор
Min. / Max. Water Pressure	20 - 120 psi
DIMENSIONS / CLEARANCES	/ WEIGHTS
Depth with Handles	29 1 / 8 "
Depth without Handles	29 1/8"
Depth without Door	24 3/4"
Depth (Total with Door Open)	43 5/8"
Height to Top of Case	68 7 / 8 ''
Height to Top of Door Hinge	70 1/4"
Width	35 3 / 4 "
Width (Door Open 90° with Handle)	44 7/8"
Width (Door Open 90° without Handle)	44 7/8"
Door Edge Clearance with Handle	4 1/4"
Door Edge Clearance without Handle	2 1/4"
Installation Clearance	Sides 1/8", Top 1", Back 2"
Approx. Weight (Product / Carton)	291 lbs. / 313 lbs.
Carton Dimensions (WxHxD)	38" x 72" x 31"
LIMITED WARRANTY	
Parts & Labor	1 Year
Sealed System (Parts & Labor)	5 Years
Compressor (Parts & Labor)	5 Years
Smart Inverter Compressor (Parts Only)	6-10 Years

*System tested and certified by NSF® International against NSF / ANSI Standard 42, Standard 53 and Standard 401.







DIMENSIONS / CLEARANCES				
Α	Depth without Handles	29 1 / 8 " (739 mm)		
В	Width	35 3 / 4 " (908 mm)		
С	Height to Top of Case	68 7 / 8 " (1750 mm)		
D	Height to Top of Hinge	70 1 / 4 " (1785 mm)		
Е	Back Clearance	2" (50 mm)		
F	Depth without Door	24 3/4" (628 mm)		
G	Depth with Handle	29 1 / 8 " (739 mm)		
Н	Depth (Total with Freezer Drawer Open)	48 7 / 8 " (1239 mm)		
I	Depth (Total with Door Open 90°)	43 5/8" (1106 mm)		

INSTALLATION NOTES

- The installation location chosen for the refrigerator should allow space behind the unit for connections and airflow and space in front to open the doors and drawers.
- Too small of a distance from adjacent items may result in lowered freezing capability and increased electricity consumption charges. Allow at least 24 inches (610 mm) in front of the refrigerator to open the doors, and at least 2 inches (50.8 mm) between the back of the refrigerator and the wall.

