



# BLACK SOLID WHITE SOLID WHITE SOLID WHOME SOLID WHOME SOLID WHOME SOLID WHOME SOLID WHITE SOLID WHITE SOLID WHITE SOLID WHITE SOLID SOLID WHITE SOLID

### **FEATURES & BENEFITS**

### PERFORMANCE

- Volume of 3.3 cu ft holds up to 35 bottles (12 oz) or 48 cans (12 oz)
- Mechanical Dial Control is conveniently located on the grille
- Temperature range: 34°F 45°F
- Passive cooling system

## INTERIOR/EXTERIOR

- Three removable tempered glass shelves
- Three fixed shelves in door
- Door swing is field reversible for non-lock models, and is shipped right-hand hinged
- Door lock models are available, and must be ordered hinge specific

### INTEGRATION


- Unit is designed to be built-in or can be freestanding
- Available in the following finishes: Black or White

### **Model Details**

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-29RB-00A	115 / 60	Field Reversible	Black Solid	89 lb
	,			
U-29RB-13A	115 / 60	Right-Hand Hinge	Black Solid (Lock)	89 lb
U-29RB-15A	115 / 60	Left-Hand Hinge	Black Solid (Lock)	89 lb
U-29RW-00A	115 / 60	Field Reversible	White Solid	89 lb
U-29RW-13A	115 / 60	Right-Hand Hinge	White Solid (Lock)	89 lb
U-29RW-15A	115 / 60	Left-Hand Hinge	White Solid (Lock)	89 lb

### **DIMENSIONS**

Dimensions shown apply to all finishes.



## Filler Panel (Not Provided by U-Line) – May Be Added Above or Below Unit to Enclose for a Built-In Look Typical Counter Height 34-1/4" (870 mm) to Sis-1/8" (867 mm) Cut-Out Height 28-5/8" (727 mm) to 28-7/8" (733 mm) Typical Counter Line Freferred location is in adjacent cabinet. (610 mm) Typical Counter Line Freferred location is in adjacent cabinet.

### **INSTALLATION NOTES**

Cutout includes the additional  $\mbox{$^{1}\!\!/\!\!4''}$  width overall to ensure proper installation.

-21-1/16" -(535 mm)

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details

### **SPECIFICATIONS**

Model	29R	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	35	
Capacity: Can (12 oz)	48	
Capacity: Volume (cu ft)	3.3	
Control Type	Mechanical Dial	
Dimensions: Product Depth	23" / 584 mm	
Dimensions: Product Height	28 ½" / 724 mm	
Dimensions: Product Width	20 7/8" / 530 mm	
Energy Consumption: Avg. Per Year	260 kWh	
ENERGY STAR / CEE RATING	ENERGY STAR / Tier 1	
Product Weight: Max	80 lb	
Refrigerant Type	R600a (1.41 oz)	
Sabbath (Star K Certified)	No	
Temperature Range	34°F - 45°F	

### **COOLING SYSTEM**



### **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized  $115\ VAC$ ,  $60\ Hz$ ,  $15\ A$  power supply (normal household current).







