



# SBC56GBINKCSSADA



32.25" x 23.38" x 23" (H x W x D)

Built-in undercounter ADA height commercially listed beer dispenser with glass door, lock, and stainless steel wrapped cabinet; no tapping equipment included

### Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

### Product Features:

|                                 |                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| ADA compliant height            | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters      |
| Commercially approved           | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings           |
| Built-in capable                | Front-breathing design allows fully recessed installation under counters                              |
| Tap kit not included            | Install your own tapping equipment to create a customized beer cooler                                 |
| Designed for 1/6 kegs           | Interior can store up to two sixtel kegs                                                              |
| Double pane tempered glass door | Heat resistant design provides clear view to promote impulse buys                                     |
| Stainless steel wrapped cabinet | Exterior features a wrapped stainless steel finish for lasting durability in busy commercial settings |
| Professional handle             | Curved towel bar style handle in brushed stainless steel                                              |
| Factory-installed lock          | Keyed lock conveniently located towards the top of the door for added security (2 keys included)      |

## SBC56GBINKCSSADA Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 32.0" (81 cm)      |
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Nominal Width              | 24.0" (61 cm)      |
| Width                      | 23.38" (59 cm)     |
| Nominal Depth              | 23.0" (58 cm)      |
| Depth                      | 23.0" (58 cm)      |
| Depth with Handle          | 25.5" (65 cm)      |
| Depth with door at 90°     | 44.5" (113 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Glass              |
| Cabinet                    | Stainless Steel    |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.8                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101062860       |
| Kegerator                  |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.67 oz.           |
| High Side PSI              | 124.0              |
| Low Side PSI               | 30.0               |
| Inter Height               | 26.0" (66 cm)      |
| Interior Width             | 21.0" (53 cm)      |
| Interior Depth             | 18.0" (46 cm)      |
| Compressor Step Height     | 7.0" (18 cm)       |
| Compressor Step Width      | 21.0" (53 cm)      |

|                       |              |
|-----------------------|--------------|
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range     | 34° to 43°F  |

