30" Electric Cooktop

- Radiant Cooktop with 4 Elements
- Steady Heat Elements
- Dual 9 3/₁₆" / 5 15/₁₆" Element
- Warming Function

COLOR AVAILABILITY

• LED Direct Touch Controls (Front)







COLORYTONIENDIENT		
CBEW3013BE - Black Ceran Glass w/Grey Pattern		
COOKTOP FEATURES		
Cooktop Type	Electric	
Number of Elements	4	
Element Size / Wattage		
Left Front	6 7 / _{16} " – 1,200W (240V)	
Left Rear	6 7 / _{16} " – 1,200W (240V)	
Center	9 15 / 16 " – 2,500W (240V)	
Right Front	Dual 9 3/ ₁₆ " / 5 15/ ₁₆ " – 2,200W / 1,000W (240V)	
Right Rear	_	
Bridge Element	No	
Hot Surface LED Indicator	Yes	
Auto Shut Off	No	
Warm Function	Yes	
Power Control	Steady Heat	
CONTROLS		
Cooktop Control Type	LED Direct Touch Controls (Front)	
Control Lock	Yes	
CONVENIENCE		
ADA Compliant	Yes	

CMART FEATURES		
SMART FEATURES		
Wi-Fi Enabled	Yes	
ThinQ® Technology	Yes	
ThinQ UP [™]	Yes	
SmartDiagnosis™	No	
FINISHES AND APPEARANCE		
Cooktop Surface	Black Ceran Glass w/Grey Pattern	
Cooktop Frame / Trim	N/A	
TECHNICAL SPECS		
ENERGY STAR® Certified	Yes	
Required Power Supply	240 / 208 V, 60 Hz, 3-Wire or 4-Wire	
Minimum Circuit Rating	40 Amp	
kW Rating at 208V	29.6 kW	
kW Rating at 240V	25.5 kW	
Power Cord / Cable	Not Included	
Power Cable Location	Right Rear	
DIMENSIONS / CLEARANCES	/ WEIGHTS	
Product Dimensions (W x H x D)	30 11/ ₁₆ " x 4 5/ ₁₆ " x 21 1/ ₁₆ "	
Cutout Dimensions (W x H x D)	28 1 / 2 " x 5 7 / 8 " x 19 5 / 8 "	
Carton Dimensions (W x H x D)	3 7/8 " x 5 3/8 " x 24 1/4 "	
Approx. Weight (Product / Carton)	34.99 lbs. / 40.7 lbs.	
LIMITED WARRANTY		
Parts and Labor	1 Year	

DIMENSIONS / CLEARANCES 30" Right side 36 ** Do not obstruct these areas. Q В Radius 3/8" (10 mm) Μ 4" x 8" (102 mm x 203 mm) opening to route armored cable if panel is present. Do not obstruct these areas. Q R 4Ο Approximate location of junction box 2 3/4" (70 mm)

Α	Width of upper plate	30 11/16" (781 mm)
В	Depth of upper plate	21 1/16 " (534 mm)
С	Distance from bottom of upper plate to bottom of conduit and terminal block enclosure	3 15/16 " (101 mm)
D	Width of cooktop base	27 15/16 " (710 mm)
E	Depth of cooktop base	18 13/₁₆" (477 mm)
F	Distance from bottom of upper plate to bottom of cooktop base	2 1/2 " (64 mm)
G	Height of conduit and terminal block enclosure	1 7/₁₆" (37 mm)
Н	Height of base cover	1 5/8" (41 mm)
I	Distance from side edge of cutout to side of counter	≥ 1 1/8 " (28 mm)
J	Width of cutout	≥ 28 1/2" (724 mm) ≤ 28 5/8" (727 mm)
K	Depth of cutout	≥ 19 5/8 " (498 mm) ≤ 19 11/₁₆ " (501 mm)
L	Depth of bottom cabinets	23 13/16" (605 mm)
М	Distance from front of counter to front edge of cutout	≥ 2 3/16" (55 mm)
N	Distance from rear edge of cutout to nearest combustible surface	≥ 2 1/16 " (52 mm)
0	Height below cutout (space is needed under cooktop for optimum performance.)	≥ 5 1/4 " (134 mm)
Р	Depth of overhead cabinets	≤ 13" (330 mm)
Q	Clearance from top of cooking surface to bottom of overhead cabinets	≥ 30" (762 mm)
R	Clearance from countertop to bottom of adjacent cabinets	≥ 18" (457 mm)
S	Junction box (approx. location)	12" (305 mm)
Т	Junction box (approx. location)	10" (254 mm)
U	Distance from edge of cooktop to nearest combustible wall (either side of unit)	≥ 2" (50 mm)

INSTALLATION NOTES

- Allow 2" (50 mm) space below the armored cable opening to clear the electric cable and allow space for installation of the junction box on the wall at the back of the cooktop.
- Thickness of glass: 3/16" (4 mm)
- Make sure the cabinets and wall coverings around the cooktop can withstand the temperatures up to 200°F generated by the cooktop.
- To eliminate the risk of burns or fire by reaching over heated surfaces, cabinet storage space located above the cooktop should be avoided. If cabinet storage is provided, risk can be reduced by installing a range hood that projects horizontally a minimum of 5" (127 mm) beyond the face of the cabinets.
- It is very important to keep 2 3/4" (70 mm) distance between the cooktop and the oven installed below it.

