

LB26H2200_

25.5 cu.ft. capacity Bottom Freezer Refrigerator

25.5 cu.ft Large Capacity

ENERGY STAR® Certified

Wi-Fi Enabled

ThinQ®

Smart Inverter Compressor

AVAILABLE COLORS

PRINTPROOF™ STAINLESS STEEL

BLACK STAINLESS STEEL



Proactive Smart Alerts to Keep Your Appliances Running Smoothly

ThinQ Care

- Preventative Alerts help you stay a step ahead of potential issues to find proactive solutions before problems arise.
- Avoid preventable repairs and service calls with real-time diagnostics for a hassle-free experience.
- Integrated within LG's ThinQ app—a smart home hub for managing your smart devices and appliances.

SUMMARY

Refrigerator (cu.ft.)	17.2
Freezer (cu.ft.)	8.3
Total Capacity (cu.ft.)	25.5

ENERGY

ENERGY STAR® Certified	Yes
Energy Consumption (kWh/Year)	562

ICE & WATER SYSTEM

Dispenser	N/A
No. Freezer Ice Maker	1
Freezer Ice Type	Cubed
Freezer Daily Ice Production	2.5 / 2.8 (Ice Plus) lbs.
Freezer Ice Storage Capacity	5.1 lbs
Ice Plus	Yes
Filteration System	1 Stage
Filter	LT1000P

COOLING

Compressor Type	Smart Inverter Compressor
Refrigerant	R600a / 70g / 2.47oz
Evaporator	1
Multi Air Flow Cooling	Yes
Temperature Sensors	2

REFRIGERATOR

No. of Shelves	4 Split (4 Fixed)
Shelf Construction	Spill Protector Tempered Glass
Shelf Trim	White décor
No. of Crisper Bins	2
Pantry (Glide N Serve)	Yes (Normal)
Cool Guard	No
Duct (Air Filter)	
[Fresh Air Filter, Multi Air Flow]	Multi Air Flow
Light	Yes
Light (Back Lit Lighting)	No
Backwall [Metallic Décor, White Decor, LED Backwall]	White décor

REFRIGERATOR DOOR

No. of Door Bins	3
Door Shape	Flat
Handle Type	Bar (New)

FREEZER

Door Type	Pull Drawer
Handle Type	Pocket Handle
Drawers / Shelves	2-Tier Organization
Drawer Divider	Yes
Freezer Light	LED Lighting
No. of Door Bins/Construction	2

DISPLAY

Display Type	Membrane/ White LED
Temperature Control	Electronic/ Digital
Door Alarm	Yes
Child Lock	Yes
Smart Diagnosis	Yes
Auto Closing Door Hinge	No
Wi-Fi Enabled	Yes
ThinQ®	Yes
ThinQ® Care (Proactive Customer Care)	Yes
Sabbath Mode	Yes
ADA Compliant	Yes
Garage Ready	No

MATERIALS & FINISH

Hidden Hinges	Yes
Surface	Smooth
Toe Grill	No
All Available Colors	PrintProof™ Stainless Steel Black Stainless Steel
Insulation	Low GWP and Zero ODP Blowing Agent

DIMENSIONS/CLEARANCES/WEIGHTS

Total (WxHxD)	32 15/16" x 69 15/16" x 35 15/16"
Width	32 15/16"
Height (Top of Hinge or Door cap Décor)	69 15/16"
Depth (with Handle)	35 15/16"
Width (Door Open 90° without Handle)	34 7/16"
Case Edge Clearance (Door Fully Open)	12 15/32"
Width (Door Open 90° with Handle)	36 13/16"
Width (Door Fully Open without Handle)	46 7/8"
Door Edge Clearance with Handle	4 1/16"
Door Edge Clearance without Handle	1 11/16"
Height to Top of Case	68 5/8"
Height (Floor to Top of Freezer Door)	27 5/8"
Depth without Door	29 1/2"
Depth without Handles	35 15/16"
Depth (to Hinge Cover)	19 5/8"
Depth (Total with Door Open)	63 1/4"
Depth (Draw Open Fully without Handle)	53 3/8"
Installation Clearance	Sides 1/8", Top 1", Back 2"
Carton Dimensions (WxHxD)	35" x 72" x 36 11/16"
Weight (Unit/Carton)	234 lb / 250lb

LIMITED WARRANTY

Parts & Labor	1 Year
Sealed System (Parts & Labor)	5 Years
Compressor (Parts & Labor)	5 Years
Inverter Compressor (Parts only)	10 Years



UPC CODES

LB26H2200S	195174122310
LB26H2200D	195174122341

KEY FEATURES

SMART APPLIANCE

PRODUCT FEATURES



DIMENSION / CLEARANCES

- Check the dimensions of the appliance and the installation path to ensure there is sufficient room to move the refrigerator through doors or narrow openings.
- If an opening is too narrow to fit the refrigerator through, remove the refrigerator doors. See Removing/ Assembling the Doors and Drawers in this manual.
- The installation location chosen for the refrigerator should allow space behind the unit for connections and airflow and space in front to open the doors and drawers.
- Too small of a distance from adjacent items may result in lowered freezing capability and increased electricity consumption charges. Allow at least 24 inches (610 mm) in front of the refrigerator to open the doors, and at least 2 inches (50.8 mm) between the back of the refrigerator and the wall.

DIMENSIONS

A	Depth without Handle	35 15/16" (913 mm)
B	Width	32 15/16" (836 mm)
C	Height to Top of Case	68 5/8" (1743 mm)
D	Height to Top of Hinge	69 15/16" (1776 mm)
E	Back Clearance	2" (51 mm)
F	Depth without Door	29 1/2" (748 mm)
G	Depth with Handle	35 15/16" (912 mm)
H	Depth (Total with Freezer Drawer Open)	54 3/8" (1381 mm)
I	Depth (Total with Door Open 90°)	63 1/4" (1606 mm)
J	Length of Power Cord	61" (1550 mm)

LEVELING THE REFRIGERATOR

The refrigerator has two front leveling legs. Adjust the legs to alter the tilt from front-to-back or side to side. If the refrigerator seems unsteady or the doors do not close easily, adjust the refrigerator's tilt, using the instructions below:

1. Turn the leveling leg to the left to raise that side of the refrigerator or to the right to lower it. It may take several turns of the leveling leg to adjust the tilt of the refrigerator.
2. Open both doors, and check to make sure that they close easily. If the doors do not close easily, tilt the refrigerator slightly more to the rear by turning both leveling legs to the left. It may take several more turns, and be sure to turn both leveling legs the same amount.

NOTE

- A flare nut wrench works best, but an open-end wrench will suffice. Do not over-tighten.

