

DAR 1120 Insert ventilation hood for perfect combination with Ranges and Rangetops.




- Customized kitchen design fully integrated in 27 1/2 (698) in (mm)
- Perfect illumination LED ClearView lighting
- Dishwasher-safe 2 high-quality stainless steel grease filters
- Safe and easy to clean Miele CleanCover
- Auto-vent safety sensor protects against overheating

EAN: 4002515446706 / Material number: 09753460 / Old Material Number: 28112050USA

Insert ventilation extractor  Required accessories Blower  Operating modes Recirculated mode External operation possible  Control panel Rotary knob  Temperature sensor Power levels (number excl. Intensive)  Cleaning convenience Dishwasher-safe grease collection channel Easy-to-clean canopy interior - CleanCover Filter system Number of dishwasher-safe stainless steel baffle filters Lighting LED ClearView lighting  Number x W  Rober options (to be purchased separately) DRIB XL internal blower in CFM (m³) DREB XL external blower in CFM (m³) Technical data Canopy width in in.(mm) Canopy depth in in.(mm) Canopy depth in in.(mm) Power wight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Fuse rating in A Voltage in V Number of vent connection in in. (mm) Poliameter of vent connection in in. (mm)	Construction type	
Required accessories Blower Operating modes Recirculated mode External operation possible Control panel Rotary knob Temperature sensor Power levels (number excl. Intensive) Cleaning convenience Dishwasher-safe grease collection channel Easy-to-clean canopy interior – CleanCover Filter system Number of dishwasher-safe stainless steel baffle filters Lighting LED ClearView lighting Number v W Blower options (to be purchased separately) DRIB XL internal blower in CFM (m³) DREB XL external blower in CFM (m³) Technical data Canopy width in in.(mm) Canopy width in in.(mm) Canopy depth in in.(mm) Canopy depth in in.(mm) Pore the dish in in. Pore the dish in extraction in in. Pore the dish in extraction in extraction in in. P		•
Blower Operating modes Recirculated mode air extraction External operation possible Control panel Rotary knob Temperature sensor Power levels (number excl. Intensive) Slay and can canopy interior – CleanCover Filter system Number of dishwasher-safe stainless steel baffle filters Lighting LED ClearView lighting LED ClearView lighting Number x W Blower options (to be purchased separately) DRIB XL internal blower in CFM (m³) Technical data Canopy width in in.(mm) Canopy width in in.(mm) Canopy depth in in.(mm) Canopy depth in in.(mm) Pate width in in.(sy) Standard plug fitted Total connected load in kW Fuse rating in A Voltage in V Number of vent connection in in. (mm) Pares Vales Poliameter of vent connection in in. (mm) Pares X (as y (		
Operating modes       air extraction         Recirculated mode       air extraction         External operation possible       •         Control panel       •         Rotary knob       •         Temperature sensor       •         Power levels (number excl. Intensive)       3         Cleaning convenience       •         Dishwasher-safe grease collection channel       •         Easy-to-clean canopy interior – CleanCover       •         Filter system       •         Number of dishwasher-safe stainless steel baffle filters       2         Lighting       •         LED ClearView lighting       •         Number x W       2 x 3 W         Blower options (to be purchased separately)       •         DRIB XL internal blower in CFM (m³)       1189         DREB XL external blower in CFM (m³)       1189         Technical data       •         Canopy width in in.(mm)       27 1/2 (698)         Canopy width in in.(mm)       27 1/2 (698)         Canopy beight in in.(mm)       17 3/4 (449)         Canopy peight in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       6 (16.0)         Length of electrical wire in ft (m)       2 (0.8)	·	•
Recirculated mode air extraction  External operation possible  Control panel  Rotary knob  Temperature sensor  Power levels (number excl. Intensive)  Cleaning convenience  Dishwasher-safe grease collection channel  Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  Lighting  LED Clear/iew lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy height in in.(mm)  Acanopy depth in in.(mm)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied		_
External operation possible  Control panel  Rotary knob  Temperature sensor  Power levels (number excl. Intensive)  Gleaning convenience  Dishwasher-safe grease collection channel  Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy height in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in Ibs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  9 7/8 (250)  Accessories supplied		air autraction
Control panel  Rotary knob  Temperature sensor  Power levels (number excl. Intensive)  Seasy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  Lighting  LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  Possible vent connection on in. (mm)  Possible vent connection at top  Possible vent connection in in. (mm)  Possib		all extraction
Rotary knob Temperature sensor Power levels (number excl. Intensive) 3 Cleaning convenience Dishwasher-safe grease collection channel Easy-to-clean canopy interior – CleanCover Filter system Number of dishwasher-safe stainless steel baffle filters Lighting LED ClearView lighting Number x W Rower options (to be purchased separately) DRIB XL internal blower in CFM (m³) DREB XL external blower in CFM (m³) 1189 Technical data Canopy width in in.(mm) 27 1/2 (698) Canopy width in inches 29 15/16 Canopy height in in.(mm) 17 3/4 (449) Canopy depth in in.(mm) 22 7/8 (579) Net weight in lbs. (kg) Length of electrical wire in ft (m) 2 (0.8) Standard plug fitted Total connected load in kW Fuse rating in A Voltage in V Number of phases Vent connection at top Diameter of vent connection in in. (mm) Polanop (120) Accessories supplied	· · · · · · · · · · · · · · · · · · ·	
Temperature sensor Power levels (number excl. Intensive) 3 Cleaning convenience Dishwasher-safe grease collection channel Easy-to-clean canopy interior – CleanCover Filter system Number of dishwasher-safe stainless steel baffle filters Lighting LED ClearView lighting Number x W Blower options (to be purchased separately) DRIB XL internal blower in CFM (m³) DREB XL external blower in CFM (m³) 1189 Technical data Canopy width in in.(mm) 27 1/2 (698) Canopy width in inches 29 15/16 Canopy height in in.(mm) 17 3/4 (449) Canopy depth in in.(mm) 22 7/8 (579) Net weight in lbs. (kg) Length of electrical wire in ft (m) 2 (0.8) Standard plug fitted 15 Voltage in V 120 Number of phases Vent connection at top Diameter of vent connection in in. (mm) 9 7/8 (250) Accessories supplied	•	•
Power levels (number excl. Intensive)  Cleaning convenience  Dishwasher-safe grease collection channel  Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  Lighting  LED ClearView lighting  LED ClearView lighting  Number x W  Plower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in inches  Canopy height in in.(mm)  Canopy depth in in.(mm)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied		
Cleaning convenience  Dishwasher-safe grease collection channel  Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  Lighting  LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in inches  Canopy height in in.(mm)  Canopy depth in in.(mm)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	<u> </u>	
Dishwasher-safe grease collection channel  Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy depth in in.(mm)  Canopy depth in in.(mm)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	,	3
Easy-to-clean canopy interior – CleanCover  Filter system  Number of dishwasher-safe stainless steel baffle filters  LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy height in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in lbs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	•	
Filter system  Number of dishwasher-safe stainless steel baffle filters  Lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  Technical data  Canopy width in in.(mm)  Canopy width in inches  Canopy width in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in lbs. (kg)  Length of electrical wire in ft (m)  2 (0.8)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied		
Number of dishwasher-safe stainless steel baffle filters  Lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in inches  Canopy width in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in lbs. (kg)  Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of vent connection in in. (mm)  9 7/8 (250)  Accessories supplied		•
LED ClearView lighting  LED ClearView lighting  Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in inches  29 15/16  Canopy height in in.(mm)  17 3/4 (449)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  36 (16.0)  Length of electrical wire in ft (m)  2 (0.8)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	•	
Number x W  Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy height in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in ins.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  Length of electrical wire in ft (m)  24 (0.8)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Vent connection at top  Diameter of vent connection in in. (mm)  2 x 3 W  2 x 3 W  2 x 3 W  1189  1189  179  189  189  27 1/2 (698)  27 1/2 (698)  29 15/16  20 17 (698)  20 15/16  21 (0.8)  21 (0.8)  22 7/8 (579)  36 (16.0)  2 (0.8)  36 (16.0)  2 (0.8)  15  10  11  11  120  Number of phases  10  11  11  120  Number of phases  Vent connection at top  9 7/8 (250)  Accessories supplied	Number of dishwasher-safe stainless steel baffle filters	2
Number x W   2 x 3 W	Lighting	
Blower options (to be purchased separately)  DRIB XL internal blower in CFM (m³)  DREB XL external blower in CFM (m³)  1189  Technical data  Canopy width in in.(mm)  Canopy width in in.(mm)  Canopy height in in.(mm)  Canopy depth in in.(mm)  17 3/4 (449)  Canopy depth in in.(mm)  22 7/8 (579)  Net weight in lbs. (kg)  Length of electrical wire in ft (m)  2 (0.8)  Standard plug fitted  Total connected load in kW  Fuse rating in A  Voltage in V  Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	LED ClearView lighting	
DRIB XL internal blower in CFM (m³)       1189         DREB XL external blower in CFM (m³)       1189         Technical data         Canopy width in in.(mm)       27 1/2 (698)         Canopy width in in.(mm)       29 15/16         Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Number x W	2 x 3 W
DREB XL external blower in CFM (m³)       1189         Technical data         Canopy width in in.(mm)       27 1/2 (698)         Canopy width in inches       29 15/16         Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Blower options (to be purchased separately)	
Technical data       27 1/2 (698)         Canopy width in in.(mm)       27 1/2 (698)         Canopy width in inches       29 15/16         Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	DRIB XL internal blower in CFM (m³)	1189
Canopy width in in.(mm)       27 1/2 (698)         Canopy width in inches       29 15/16         Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	DREB XL external blower in CFM (m³)	1189
Canopy width in inches       29 15/16         Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Technical data	
Canopy height in in.(mm)       17 3/4 (449)         Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       •         Vent connection at top       •         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Canopy width in in.(mm)	27 1/2 (698)
Canopy depth in in.(mm)       22 7/8 (579)         Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       •         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       Vent connection at top         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Canopy width in inches	29 15/16
Net weight in lbs. (kg)       36 (16.0)         Length of electrical wire in ft (m)       2 (0.8)         Standard plug fitted       ●         Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       Vent connection at top         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Canopy height in in.(mm)	17 3/4 (449)
Length of electrical wire in ft (m)  Standard plug fitted  Total connected load in kW  0.80  Fuse rating in A  15  Voltage in V  120  Number of phases  1  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	Canopy depth in in.(mm)	22 7/8 (579)
Standard plug fitted  Total connected load in kW  Fuse rating in A  15  Voltage in V  120  Number of phases  1 Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	Net weight in lbs. (kg)	36 (16.0)
Total connected load in kW       0.80         Fuse rating in A       15         Voltage in V       120         Number of phases       1         Installation notes       Vent connection at top         Vent connection at top       ●         Diameter of vent connection in in. (mm)       9 7/8 (250)         Accessories supplied	Length of electrical wire in ft (m)	2 (0.8)
Fuse rating in A  Voltage in V  120  Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	Standard plug fitted	•
Voltage in V 120  Number of phases 1  Installation notes  Vent connection at top •  Diameter of vent connection in in. (mm) 9 7/8 (250)  Accessories supplied	Total connected load in kW	0.80
Number of phases  Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied	Fuse rating in A	15
Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied  9 7/8 (250)	Voltage in V	120
Installation notes  Vent connection at top  Diameter of vent connection in in. (mm)  Accessories supplied  9 7/8 (250)	Number of phases	1
Diameter of vent connection in in. (mm) 9 7/8 (250)  Accessories supplied	Installation notes	
Diameter of vent connection in in. (mm) 9 7/8 (250)  Accessories supplied	Vent connection at top	•
Accessories supplied		9 7/8 (250)
·	,	
	Non-return flap	•



DAR 1120 Insert ventilation hood for perfect combination with Ranges and Rangetops.



DAR1120 (installation drawing)