


# MODELS RMDD3004EX, RMDD3604EX, RMDD4804EX DOWNDRAFT

For use with external blowers.



**Exhaust your cooktop without the use of an over-head hood. Control a powerful external blower from the cooktop location. Compact design is installed directly behind cooktop.**

### FEATURES

#### HOUSING:

- Rugged steel construction
- Silver paint and/or galvanized finish
- Space-saving - can be used with most cooktops on the market
- 30", 36", or 48" widths - Fits standard-size cabinets
- For indoor use only

#### CHIMNEY ASSEMBLY:

- Brushed stainless steel cover - just press button to turn unit "ON"
- Chimney rises 9½" when activated - ideal for large pots and pans
- Stylish, stainless steel filters with aluminum mesh - easy to remove and dishwasher-safe
- Stainless steel chimney front and back - makes cleanup quick and easy
- Flush-mounted, infinite rotary speed blower control
- Heat Sentry™ adjusts speed of blower to HIGH in case of excess heat
- Conveniently located button - press to lower air vent and turn unit "OFF"
- OPTIONAL Remote Control (Model RMDDRBK) activates downdraft from alternate location

#### DUCT CONNECTOR HOUSING:

- Rugged steel construction with galvanized finish
- 3¼" x 14" rectangular duct connector (8" round duct using Model 459 transition)
- 3-position discharge - movable to adjust to floor joists

### TYPICAL SPECIFICATION

Downdraft blower system shall be Broan Elite Model RMD-D3004EX (RMDD3604EX) (RMDD4804EX).

Unit shall be for indoor use only.

Unit to have steel housing with silver paint or galvanized finish. Air vent to rise at least 9½" and have a stainless steel front and back for ease of cleaning.

Filters to be stainless steel with aluminum mesh, easy to remove and dishwasher-safe.

3¼" x 14" duct connector shall be adjustable to accommodate ductwork from left, right, or below and have 7½" side to side adjustment.

Unit must accept an optional remote control activation button.

Unit to include Heat Sentry™, to adjust blower speed to HIGH in case of excess heat.

Downdraft system shall operate on 120 VAC and be able to be plugged into a standard grounded outlet. It will have an infinite speed blower control.

### SPECIFICATIONS

| VOLTS | HZ | AMPS | DUCT      |
|-------|----|------|-----------|
| 120   | 60 | 6    | 3¼" x 14" |



Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711  
Broan-NuTone Canada, Inc. Mississauga, Ontario www.broan.ca 877-896-1119

| REFERENCE | QTY. | REMARKS | Project           |
|-----------|------|---------|-------------------|
|           |      |         | Location          |
|           |      |         | Architect         |
|           |      |         | Engineer          |
|           |      |         | Contractor        |
|           |      |         | Submitted by Date |

