QUICK REFERENCE GUIDE > RGV3-488L Date: 11.09.2025 > 1

48" Series 7 Professional 8 Burner Gas Range, LPG

Series 7 | Professional



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- · Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 "

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

17000 BTU
13000BTU
13000BTU
13000BTU
13000BTU
15000BTU
15000BTU
17000BTU
17000BTU
116000 BTU
5
5.3 cu ft

Cleaning

Total capacity second oven

Usable capacity (main oven)

Easy clean porcelain basepan

2.4 cu ft

3.9 cu ft

Controls

Electric circuit 3 wire

Metal illuminated dials

•

QUICK REFERENCE GUIDE > RGV3-488L Date: 11.09.2025 > 2

Gas Requirements		Convection bake	•	ADA compliant	•
Fitting and pipe	½ NPT, min. 5⁄8″ ∑ flex line	Slow cook	•	Full extension telescopic sliding shelves	•
Supply Pressure (LPG)	11" to 14" W.C				
		Power Requirements		Secondary oven features	
Mala and factors		Service	15 A	3/4 Extension racks	2
Main oven features		Supply frequency	60 Hz	Electronic oven control	•
Broil pan	•	Supply voltage	120 V	Internal light	•
Electronic oven control	•				
Full extension telescopic racks	•				
Internal light	•	Product Dimensions		Secondary oven functions	
		Depth	29 1/8 "	Bake	•
		Depth (excluding handles)	29 1/8 "	Convection bake	•
Main oven functions		Height	35 3/4 - 36 3/4 "	Number of secondary oven functions	4
Bake	•	Width	47 7/8 "	Proof	•
Broil	•			Slow cook	•
Convection bake	•				
Number of oven functions	4	Rangetop features			
Slow cook	•	Sealed range top	•	SKU	82974
		Vent trim included	•	SNU	02974
Oven features				The product dimensions and specifications in this page apply to the sp	ecific
Auto re-ignition system	•	Recommended Back Guards Ventilation		product and model. Under our policy of continuous improvement, thes	
Electronic oven control	•	Combustible situation	BGRV3-3048H	dimensions and specifications may change at any time. You should the check with Fisher & Paykel's Customer Care Centre to ensure this page	
Full extension telescopic sliding shelves	•	Non combustible situation	BGRV2-3048 /	correctly describes the model currently available. © Fisher & Paykel	
Titanium coated, illuminated metal dials	•		BGRV2-1248	Appliances Ltd 2020	
Oven functions		Recommended hood	HCB48-12_N (48" Professional Range Hood, Dual Blower)	Other product downloads available at fisherpaykel.com	
Bake	•			$\underline{\downarrow}$ Installation Guide EN	
Broil	•	Safety			
				→ Planning Guide Professional Style Dial/Handle Accesso	ries

QUICK REFERENCE GUIDE > RGV3-488L Date: 11.09.2025 > 3



Revit

Rhino

Right To Repair Declaration (English, French)

↓ SketchUp

↓ User Guide EN

↓ User Guide FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com