

KMR 1356-3LP GD EDST/CLST RangeTop



- Professional design 48 (1219) in (mm) wide in stainless steel with Clean Touch Steel™ finishing
- Direct control metal knobs with light ring
- Easy cleaning ComfortClean dishwasher-safe grates
- Broad performance spectrum burner w. up to 19,500 BTU (5.7 kW)
- Convenient and safe automatic re-ignition for all burners

EAN: 4002516495468 / Material number: 11852660 / Old Material Number: 26135671USA

Heating type	
Fuel type	Gas
Construction type	
Rangetop	<u> </u>
Design	
Casing	Stainless steel
Front panel	CleanSteel
Genuine metal knobs	•
Cast iron pot rest (matte black enameled)	•
Cooktop features	
ReStart	•
Ring features	
Number of gas burners	6
Number of griddle surfaces	1
1st cooking zone/cooking area	
Position	front left
Туре	Ultra high-speed burner
Minimum power output in BTU/hr	1500
Max. rating in W	5700
Maximum power output in BTU/hr	19500
2nd cooking zone/cooking area	
Position	rear left
Туре	High-speed burner
Minimum power output in BTU/hr	1500
Max. rating in W	2900
Maximum power output in BTU/hr	12500
3rd cooking zone/cooking area	
Position	left center
Туре	Griddle surface
Max. rating in W	4200
Maximum power output in BTU/hr	14300
4th cooking zone/cooking area	
Position	Rear center right
Туре	Ultra high-speed burner
Minimum power output in BTU/hr	1500
Max. rating in W	3800
Maximum power output in BTU/hr	19500
5th cooking zone/cooking area	
Position	rear right
Туре	High-speed burner
Minimum power output in BTU/hr	1500
Maximum power output in BTU/hr	12500
Max. rating in W	2900
6th cooking zone/cooking area	
Position	front right
Туре	Ultra high-speed burner
Minimum power output in BTU/hr	1500
Maximum power output in BTU/hr	19500



KMR 1356-3LP GD EDST/CLST RangeTop




EAN: 4002516495468 / Material number: 11852660 / Old Material Number: 26135671USA

7th cooking zone/cooking area	
Position	Center right front
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1500
Maximum power output in BTU/hr	19500
Max. rating in W	5700
8th cooking zone/cooking area	
True Simmer function	•
Width of griddle surface in in.(mm)	10 1/4 (258)
Depth of griddle surface in in.(mm)	17 1/8 (434)
Control panel	
Operation via genuine metal knobs with backlit	•
Cleaning convenience	
Dishwasher-safe trivets	•
Single-piece cooktop surround	•
Technical data	
Width in in. (mm)	48 (1219)
Height in in. (mm)	7 5/8 (191)
Dimensions (depth) in in. (mm) with bullnose	27 1/4 (692)
Appliance depth in in. (depth) without bullnose	25 5/8 (650)
Total output in BTU/hr	117300
Weight in kg	171 (78)
Total rated load in kW	34.40
Voltage in V	120
Fuse rating in A	10
Number of phases	1
Power cord length in ft. (m)	3 (1.2)

Miele

KMR 1356-3LP GD EDST/CLST RangeTop



KMR 1354 G/LP, KMR 1355 G/LP, KMR 1356 G/LP (installation drawings)

1) Side view, 2) Front view, 3) Rear view, 4) Gas connection, 5) Electrical connection,