QUICK REFERENCE GUIDE > RS3084SRK1

30" Series 9 Integrated Column Refrigerator

Series 9 | Integrated




Install it separately or pair with another Column for seamless integration - this model is right hinge with stainless steel interior.
p>

- ActiveSmart[™] technology helps keep food fresher for longer by constantly maintaining the ideal temperature
- Two separate Variable Temperature Zones: each with Fridge, Pantry or Chill
- Customize with your own kitchen cabinetry or purchase our stainless steel door panel accessory

DIMENSIONS





FEATURES & BENEFITS

Variable Temperature Zones

Food is stored in two separate zones. You have the choice of three food modes: Fridge 32°F to 44°F, Pantry 52°F to 56°F and Chill 29°F to 32°F.

Mix & Match

Integrated Column Refrigeration gives you the freedom to mix and match. Different sized Column Fridges and Freezers can be installed separately or paired. Finish them with our stainless steel door panels or customize to match your own kitchen cabinetry.

Clever Energy

Our Energy Star certified ActiveSmart™ Foodcare Fridges & Freezers adapt to daily use by cooling and defrosting only when needed. This means your refrigerator uses the energy it needs without compromising on food care.

Appealing Illumination

Bright LEDs light up the ceiling, shelves, bins and tray in both refrigerator and freezer, making it easy to find your food and creating a welcoming glow in your kitchen for those midnight snacks.

Design Quality

The premium design and quality finish includes a steel interior lining as well as soft-close, full extension metal shelf runners for easy access and robust glass shelving.

Easy Install

Integrated Column Refrigerators and Freezers have been developed to make their installation easy. The joiner kit is included when pairing refrigerator and freezers. All models come with front adjustable levelling feet and they've been designed to easily slide into place as separate units.

Perfect Fit

These models fit flush and have only ½" gaps around them with no visible hinges or grilles. Our Integrated Column models can be seamlessly hidden behind your cabinetry or you can purchase our stainless steel door panel.

SPECIFICATIONS

Accessories (sold separately)

Door panel stainless steel Left hinge 84" RD3084L4D

Door panel stainless steel Right hinge 84" RD3084R4D

Handle kit Classic AHCLRDSF

Handle kit Contemporary round, aluminium AHSRDSF

Handle kit Contemporary square fine, aluminium	AHD5RDSF	Adjustable door shelves	4	Product Dimensions		
Handle kit Contemporary square fine, black	AHD5RDSFB	Adjustable glass cantilevered shelves	•	Depth	24 "	
Handle kit Professional round flush	AHP3RDSF	Covered door shelves	1	Height	84 "	
		Door alarm	•	Width	29 3/4 "	
Handle kit Professional round flush, Brass off-stands	AHP3RDSFBA	Fruit and vegetable bins	4			
Handle kit Professional round flush, Dark Copper off-stands	AHP3RDSFDC	Gallon door shelves	1	Parado et information		
Joiner Kit	AJ-RS84LR	LED bin lighting	•	Product information		
Toe kick stainless steel 30"	AKRS3004	LED ceiling lighting	•	Packaged weight	309 lbs	
Toe kick stainless steel 48"	AKRS4804	LED lighting	•	Unpackaged weight	294 lbs	
	AKRS5404	LED side lighting	•			
Toe kick stainless steel 54"		SmartTouch interface at counter height	•			
Toe kick stainless steel 60"	AKRS6004	Soft-close fruit and vegetable bins	•	Safety and compliance		
Toe kick stainless steel 66"	AKRS6604	Stackable bottle holders	4	ADA compliant	•	
Toe kick stainless steel 72"	AKRS7204					
Toe kick stainless steel 78"	AKRS7804					
Toe kick stainless steel 84"	AKRS8404	Performance				
Water filter replacement	847200 - FWC3	ActiveSmart™ Foodcare	•	SKU	26897	
		Dual evaporator	•			
Compathy		Humidity control system	•	The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these		
Capacity		Inverter controlled compressor	•			
Total gross capacity	16.3 cu ft	Sabbath mode	•	dimensions and specifications may change at any		
Volume	16.3 cu ft	Variable food modes	Pantry; Fridge;	check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel		
Volume refrigerator	16.3 cu ft		Chill	Appliances Ltd 2020		
		Variable temperature zones	2			
Consumption				Other product downloads available at fish	erpaykel.com	
Energy rating	Energy Star	Power Requirements				
Energy usage	247kWh/year	Rated current	10 A			
In-use energy carbon emissions estimate	87.1kgCO2e/year	Supply frequency	60 Hz		ator	
5 5 5 5 5 65		Supply voltage	115 V	± Energy Label		
				Revit Refrigerator		
Features		_		Rhino Refrigerator		
				★ Rhino Refrigerator		

QUICK REFERENCE GUIDE > RS3084SRK1 Date: 11.09.2025 > 3

 \overline{ullet}

Rhino Refrigerator

 \downarrow

Rhino Refrigerator

 $\overline{\mathbf{\Lambda}}$

Rhino Refrigerator

 $\overline{\mathbf{\Lambda}}$

Right To Repair Declaration (English, French)

 $\overline{\mathbf{V}}$

SketchUp Refrigerator

<u>↓</u>

SketchUp Refrigerator

 \overline{ullet}

SketchUp Refrigerator

 \downarrow

SketchUp Refrigerator

<u>_</u>

SketchUp Refrigerator

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com