









Stainless Solid





Integrated Solid



BrightShield protects against viruses, bacteria, mold, & mildew. Available on select models.

# **Additional Options**

Accessory panels are designed for easy installation on Integrated models



Panel

## **Key Features**

- Industry Leading: BrightShield antimicrobial lighting creates a clean environment for food and beverages \*\*select models
- Industry Exclusive: Full-depth lower interior maximizes storage options
- Industry Leading: Variable speed compressor delivers maximum energy efficiency, faster temperature response, and quieter operation
- Stainless steel interior
- Stainless steel cabinet, toe kick, and accents
- U-Adjust™ Interior: 19 adjustable positions
- Three removable, full-extension Slide & Secure™ Bins
- Convection cooling system provides a quick cool down and consistent temperature

- Temperature range: 33°F to 70°F
- Adjustable bright white or blue LED lighting (on non-BrightShield models)
- Soft close door with articulating hinge
- Volume of 5.2 cu ft holds up to 94 bottles (12 oz) or 148 cans (12 oz)
- Digital touch pad control with blue LED display
- Stainless steel handle (1/8" diameter)
- Integrated model requires 3/4" custom door panel and handle (not supplied by U-Line)
- Field reversible door is shipped right-hand hinged
- Built-in or freestanding
- Four adjustable leveling legs


### **Model Details**


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHRE524-SG01A	115 / 60	Field Reversible	Stainless Frame	163 lb
UHRE524-SG81A **BrightShield Lighting	115 / 60	Field Reversible	Stainless Frame	163 lb
UHRE524-SS01A	115 / 60	Field Reversible	Stainless Solid	148 lb
UHRE524-SS81A **BrightShield Lighting	115 / 60	Field Reversible	Stainless Solid	148 lb
UHRE524-IG01A	115 / 60	Field Reversible	Integrated Frame	156 lb
UHRE524-IG81A **BrightShield Lighting	115 / 60	Field Reversible	Integrated Frame	156 lb
UHRE524-IS01A	115 / 60	Field Reversible	Integrated Solid	139 lb
UHRE524-IS81A **BrightShield Lighting	115 / 60	Field Reversible	Integrated Solid	139 lb

### **Accessories**

Model	Description	Finish	Shipping Weight
ULAGRILLE24	Adjustable Grille (Accepts Integrated Panel)	Black	3 lb
ULASHP24FRAME*	Stainless Handleless Panel Frame	Stainless	10 lb
ULASHP24SOLID*	Stainless Handleless Panel Solid	Stainless	15 lb









# **Specifications**

Model	HRE524	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	94	
Capacity: Can (12 oz)	148	
Capacity: Volume (cu ft)	5.2	
Capacity: Wine Bottle (750 ml)	N/A	
Dimensions: Product Depth	22 <sup>15</sup> / <sub>16</sub> " / 583 mm	
Dimensions: Product Height (Min.)	33 <sup>11</sup> / <sub>16</sub> " / 855 mm	
Dimensions: Product Width	23 %" / 600 mm	
Energy Consumption: Avg. Per Year	275 - 305 kWh	
ENERGY STAR (glass door)	No	
ENERGY STAR (solid door)	Yes	
Product Weight: Max	163 lb	
Refrigerant Type:	R600a (1.34 oz)	
Sabbath (Star K Certified)	Yes	
Temperature Range	33°F - 70°F	

## Back



## **Cabinet Cut-Out**



### **Warranty**

- 2 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details



### **Installation Notes**

- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow









