30" Series 9 Integrated Warming Drawer

Series 9 | Integrated



Keep plates warm until ready to serve; rapid proof or slow cook. Panel-ready, you can match it with your cabinetry.

- Integrate your warming drawer into your surrounding cabinetry for seamless design
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- · Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DII	MEI	NSI	ON	S

Height	10 11/16 "
Width	28 7/16 "
Depth	22 3/16 "

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer is panel ready with push-to-open, to blend seamlessly behind cabinetry.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories (included)

Wire shelf	1
------------	---

Accessories (sold separately)

Handle kit Contemporary square fine, aluminium	Part 82105 (optional)
Handle kit Contemporary square fine, bla	eck Part 82103 (optional)
Handle kit Contemporary square, alumin	ium Part 82214 (optional)
Handle kit Professional round flush	Part 82139 (optional)

Capacity

Accessory rack maximum allowable weight	42lb
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55 lbs
Place settings	16
Usable depth	16 1/16 "
Usable height	9 1/16 "
Usable width	27 1/2 "

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback

Automatic timers

30', 45', 1h, 2h,
4h, 6h

QUICK REFERENCE GUIDE > WB30SDEI1

B	
Pre-set heating functions	•
Push-to-open drawer	•
Standby mode	•
Functions	
Cups	
Dehydrate	
Number of functions	ϵ
Plates	•
Rapid proof	•
Slow cook	•
Warm	•
Performance	
Heated glass base and fan Low temperature cooking Temperature levels	
Low temperature cooking Temperature levels Temperature range	95°F-185°F
Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power Requirements	95°F-185°F
Heated glass base and fan Low temperature cooking Temperature levels Temperature range	95°F-185°F 10 A 3-prong
Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power Requirements Amperage	

Adjustable front door panel to align with surrounding cabinetry	•
Depth	22 3/16 "
Height	10 11/16 "
Width	28 7/16 "
Safety	
•	
Safety Automatic turn off after 12 hours Full extension slides	•

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

SKU

$\overline{1}$	2D-DWG Integrated Warming Drawer
<u>↓</u>	2D-DXF Integrated Warming Drawer
<u> </u>	Archicad Integrated Warming Drawer
<u> </u>	Data Sheet Integrated Warming Drawer
<u>↓</u>	Installation Guide
<u> </u>	Planning Guide Professional Style Dial/Handle Accessories
<u>↓</u>	Revit Integrated Warming Drawer
<u>↓</u>	Rhino Integrated Warming Drawer
<u> </u>	Right To Repair Declaration (English, Canadian French)
<u>↓</u>	Sketchup Integrated Warming Drawer



User Guide (English)



82114

User Guide FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

 ${f T}$ 1.888.936.7872 ${f W}$ www.fisherpaykel.com