



# SBC58BLIFFLTWADA



32" x 23.63" x 22.38" (H x W x D)

Built-in 24" wide ADA-compliant dual tap beer dispenser with panel-ready door and removable tap system for non-permanent installation

**Highlights:**

Innovative Floating Tap lets you create a complete undercounter kegerator without modifying your countertop

Easy-to-install + removable tap system allows you to change your space as needed

Just 32" high for an easy fit under lower ADA compliant counters

**Product Features:**

|                                               |                                                                                                                                                                                                                                                               |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 24" Wide Built-In Floating Tap Beer Dispenser | Dual tap kegerator with a remote tapping system that includes everything you need to pour draft beer without modifying your countertop                                                                                                                        |
| Patent pending commitment-free design         | Non-permanent draft tower is separated from the actual kegerator and designed for temporary installation on counter surfaces, allowing you to remove as needed                                                                                                |
| ADA compliant design                          | 32" height allows easy installation under lower ADA compliant counters                                                                                                                                                                                        |
| Built-in capable                              | Designed for installation under the counter                                                                                                                                                                                                                   |
| No drilling needed                            | Tower is connected to the removable tap kit that does not need to be permanently attached to your countertop                                                                                                                                                  |
| Panel-ready door                              | Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Dual tap system                               | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs                                                                                                                                                                                         |
| Easy installation                             | No tools or equipment needed for fast setup and easy removal                                                                                                                                                                                                  |
| Convertible to a refrigerator                 | Includes a tap hole cover, glass shelves, and a scalloped steel bottle rack to all you to convert the kegerator into a traditional all-refrigerator                                                                                                           |



SBC58BLIFFLTWADA Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Nominal Height             | 32.0" (81 cm)       |
| Height of Cabinet          | 31.88" (81 cm)      |
| Height to Hinge Cap        | 32.0" (81 cm)       |
| Nominal Width              | 24.0" (61 cm)       |
| Width                      | 23.63" (60 cm)      |
| Depth                      | 22.38" (57 cm)      |
| Depth with Handle          | 24.3" (62 cm)       |
| Depth with door at 90°     | 44.5" (113 cm)      |
| Capacity                   | 5.8 cu.ft. (164 L)  |
| Defrost Type               | Automatic           |
| Door                       | Panel-Ready         |
| Cabinet                    | Black               |
| US Electrical Safety       | ETL                 |
| Canadian Electrical Safety | ETL-C               |
| Sanitation                 | ETL-S               |
| Energy Usage/Year          | 239.0kWh/year       |
| Amps                       | 0.8                 |
| Voltage/Frequency          | 115 V AC/60 Hz      |
| Weight                     | 180.0 lbs. (82 kg)  |
| Parts & Labor Warranty     | 1 Year              |
| Compressor Warranty        | 5 Years             |
| UPC                        | 761101145587        |
| Kegerator                  |                     |
| Door Swing                 | RHD                 |
| Reversible                 | Factory Reversible  |
| Height Adjustable          | No                  |
| Tap Kit                    | Yes                 |
| Number of Taps             | 2                   |
| Adjustable Shelves         | Yes                 |
| Shelf Type                 | Glass and Scalloped |
| Shelf Qty                  | 4                   |
| Thermostat Type            | Dial                |
| Interior Light             | Yes                 |
| Refrigerant                | R600a               |
| Refrigerant Amount         | 0.64 oz.            |
| Inter Height               | 27.0" (69 cm)       |
| Interior Width             | 21.0" (53 cm)       |

|                        |                |
|------------------------|----------------|
| Interior Depth         | 17.75" (45 cm) |
| Compressor Step Height | 6.5" (17 cm)   |
| Compressor Step Width  | 21.0" (53 cm)  |
| Compressor Step Depth  | 5.5" (14 cm)   |
| Level Legs Qty         | 4              |
| Temperature Range      | 36 to 46°F     |

