

2013 AUDIO SC-HTB770 HOME THEATER SYSTEM



Additional Color Option: Silver 

3.1CH 55" MATCHING MULTI-POSITIONAL SOUND BAR

Detachable 3.1ch speaker system configuration easily conforms to TV screens up to 55".

CLEAR MODE DIALOG

Gives the sound greater depth and makes voices sound lifelike.


HDMI SWITCHING 3 INPUTS / 1 OUTPUT

Connect three HDMI source components into the system for easy switching and less wire clutter.

- LincSD-Amp¹
- 3.1 Channel System
- Clear Mode Dialog
- Dialog Level Control
- Down Firing Subwoofer
- Low Power Consumption
- Energy Star[®] Qualified 300W

- Hairline Finish
- Stainless Mesh
- Slim Stylish Design
- Visible Speaker
- Suitable for 55- to 65-inch TV
- Multi-positional Speaker Design
- Wireless Subwoofer

- Auto Gain Control
- VIERA Link[™]
- Audio Return Channel (ARC)²
- Compatible with 3D Signal
- Wireless Music Streaming with Bluetooth[®] Technology



¹This function is the same as that equipped in the Anti-Jitter Digital Amplifier introduced in 2012.
²ARC compatible TV is required.

2013 AUDIO SC-HTB770 HOME THEATER SYSTEM

AUDIO SYSTEM			
Output Channel			3.1ch
Power Output	Home Theater Mode (RMS)	Total Power	300W
		Front / Center	60W x 3 (1kHz, 6ohms, 10% THD)
		Subwoofer	120W (100Hz, 8ohms, 10% THD)
Power Output	Home Theater Mode (FTC)	Total Power	115W
		Front / Center	25W x 3 (120Hz-20kHz, 6ohms, 1% THD)
		Subwoofer	40W (60-120Hz, 8ohms, 1% THD)
Dolby® Digital			•
Dolby® Pro Logic® II / Dolby® Virtual Speaker			•
DTS™			•
HIGH QUALITY PICTURE			
FULL HD 3D Compatible			•
1080p Output (x.v.Color™, Deep Color)			•
HIGH QUALITY SOUND			
LincsD-Amp			•
Clear-mode Dialog			•
Dialog Level Control			•
Anti-vibration Integrated Subwoofer			—
Down Firing Subwoofer			•
Up to 7.1ch Linear PCM Input via HDMI			•
EASY OPERATION			
Multi-positional Speaker Layout			3.1ch
Multi-angle Position Layout			—
Wireless Subwoofer			•
Auto Gain Control			•
ARC (Audio Return Channel)			•
IR Blaster Included			—
VIERA Link™ (HDAVI Control 5)			•
Wall-mountable Speaker			•
NETWORKING			
Bluetooth® Wireless Technology			•
SPEAKER SYSTEM			
Front	Configuration		3-way 3 speakers, Bass-reflex
	Speaker Unit [Approx.]		Woofer: 2-1/4" (5.7 cm) Cone Type x 2 Tweeter: 1" (2.5 cm) Semi-dome Type x 2 Super Tweeter: Piezo Type x 2
Center	Configuration		2-way 2 speakers, Bass-reflex
	Speaker Unit [Approx.]		Woofer: 2-1/4" (5.7 cm) Cone Type Super Tweeter: Piezo Type
Subwoofer	Configuration		1-way 1 speaker, Bass-reflex (Down Firing)
	Speaker Unit [Approx.]		Woofer: 6-1/2" (16cm) Cone Type
TERMINAL			
HDMI Output			• (TV)
HDMI Input			• (3) (BD / DVD, AUX1, AUX2)
Optical Input			• (2) (TV, AUX3)
Analog Audio Input	RCA		—
	3.5mm		—
OTHERS			
Power Supply			AC 120V, 60Hz
Power Consumption [Approx.]	Total	Normal Use [Approx.]	57W
		Standby [Approx.]	0.45W
	Main Unit	Normal Use [Approx.]	37W
		Standby [Approx.]	0.25W
	Subwoofer	Normal Use [Approx.]	20W
		Standby [Approx.]	0.2W
Suitable TV Sizes			55"-65"
DIMENSIONS, WEIGHT			
Main Unit		Dimensions (W x H x D)* [Approx.]	12-3/16 x 1-12/16 x 7-6/16 inch (310 x 45 x 188 mm)
		Weight [Approx.]	2.54 lbs. (1.15 kg)
Front	Horizontal Placement (for wall-mount)	Dimensions (W x H x D) [Approx.]	48-7/16 x 2-11/16 x 1-10/16 inch (1230 x 68 x 41 mm)
		Weight [Approx.]	4.37 lbs. (1.98 kg)
	Vertical Placement (with stand)	Dimensions (W x H x D) [Approx.]	5-13/16 x 21-12/16 x 5-13/16 inch (148 x 552 x 148 mm)
		Weight [Approx.]	1.96 lbs. (0.89 kg)
	Rack Top Layout (without stand)	Dimensions (W x H x D) [Approx.]	—
		Weight [Approx.]	—
Subwoofer		Dimensions (W x H x D) [Approx.]	7-3/32 x 16-1/16 x 12-1/16 inch (180 x 408 x 306 mm)
		Weight [Approx.]	10.50 lbs. (4.76 kg)

*1 Excluding the projecting parts.

Specifications are subject to change without notice. Weight and dimensions are approximate.