

## LAYERS ISLAND

Robert Brunner's bold re-imagining of a classic island range-hood form is a streamlined fusion of black or white glass and stainless steel. A slim profile and a quartet of halogens enhance the floating effect to lend new meaning to leading edge. Optional duct cover extensions can accommodate contemporary loft-style kitchens with ceilings of up to 12 feet.



	SIZE	NET WIDTH	COLOR
<b>ALL-M90ABX</b>	36"	35 7/16"	Stainless Steel/Black Glass
<b>ALL-M90AWX</b>	36"	35 7/16"	Stainless Steel/White Glass
<b>ALL-E42ABX</b>	42"	42"	Stainless Steel/Black Glass
<b>ALL-E42AWX</b>	42"	42"	Stainless Steel/White Glass



RF Remote Control

# ARC COLLECTION

## LAYERS ISLAND

### MODEL

ALL-M90ABX	36"
ALL-M90AWX	36"
ALL-E42ABX	42"
ALL-E42AWX	42"

### FEATURES

Controls	Memory Touch Glass
Speed Levels	3
Auto Delay-Off	Yes
CleanAir Function	Yes
Remote Control	Yes, RF
Lighting	Halogen, 20W x 4
Tri-Level Lighting	Yes
Filters	Decorative Mesh x 2
Recirculating	Yes
Duct Cover Extension	Yes

### \*PERFORMANCE

Internal Blower - CBI-290A	200 - 290 CFM, 1.4 - 3.2 Sones
Internal Blower - CBI-600A	240 - 600 CFM, 1.8 - 6 Sones
In-Line Blower - PBN-1000A	500 - 1000 CFM, Sones NA
External Blower - CBE-1000	500 - 1000 CFM, Sones NA

### AC INPUT

120V - 60Hz

### \*\*AC POWER

Hood Only Max. 80W, 0.66 Amps

### MOUNTING HEIGHTS

Height from the cooking surface Min. 24" - Max. 36"

### HOOD HEIGHTS

#### Standard

Minimum Ducted	30"
Minimum Recirculating	30"
Maximum	34"

#### Short Kit - Z1C-00LL

Minimum Ducted	37 1/2"
Minimum Recirculating	37 1/2"
Maximum	49"

#### Long Kit - Z1C-01LL

Minimum Ducted	53 1/2"
Minimum Recirculating	53 1/2"
Maximum	79"

### DUCT SPECIFICATIONS

Vertical - Internal	6"
Vertical - In-Line/External	10" to 8"***
Horizontal	NA

### OPTIONAL ACCESSORIES

Recirculating Kit	ZRC-00LL
Duct Cover Extension Kit, Short (8 1/2' - 9 1/2' ceiling)	Z1C-00LL
Duct Cover Extension Kit, Long (9 1/2' - 12' ceiling)	Z1C-01LL

\*Requires purchase of Zephyr blower, sold separately. \*\*AC power listed above is for hood with lights only. See blower specs on our website for more AC power details. \*\*\*10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with the external and in-line blowers.

